Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

DISTRICT I P.O. Box 1980, Hobbs, NM 88240	2040 Pacheco St. Santa Fe, NM 8750		WELL API NO. 30-025-04717	
DISTRICT II P.O. Drawer DD, Artesia, NM 88210			5. Indicate Type of Lease STATE FEE	_
DISTRICT III			6. State Oil & Gas Lease No.	
1000 Rio Brazos Rd., Aztec, NM 87410	CES AND REPORTS ON WELL	S		i india
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name	
1. Type of Well: OIL GAS WELL WELL		'&A'd Well	Devonian State	
2. Name of Operator Citation Oil & Gas Corp.			8. Well No.	
3. Address of Operator 8223 Willow Place South, Suite 250, Houston, Texas 77070-5623			9. Pool name or Wildcat	
8223 Willow Place South, Sui 4. Well Location	e 250, Houston, Texas 77070-562	23	Eumont Yates Seven Rivers Queen	
Unit Letter J: 198	O Feet From The South	Line and 198	Feet From The East	Line
Section 20			NMPM Lea Cou	inty
	10. Elevation (Show whether L 3612' (estimated)			
11. Check	Appropriate Box to Indicate			
NOTICE OF INT	ENTION TO:	SUBS	SEQUENT REPORT OF:	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING	
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING	OPNS. PLUG AND ABANDONMENT	
PULL OR ALTER CASING		CASING TEST AND CEM	ENT JOB	
OTHER:		OTHER:	Well on production	
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Set 5-1/2" CIBP @3300' & perf'd Yates 3030' - 3225' with 1 spf; .38", 31 holes total. Spotted 250 gallons acid across perfs and set pkr @2835'. Acidized with 1500 gals 15% NEFe Hcl; frac'd with 21442 gals 40# linear gel foamed with 50.5 tone CO2, carrying 81040# 12/20 mesh Brady sand tagged with .5 mc IR-192 RA material. RD 10/6/97 and cleaned out frac sand from 3032' - 3300' (CIBP) using 4% Kcl wtr foamed with N2.; drilled on CIBP @3300' and set down @3578'. Circulated hole clean. Ran in hole with 2-3/8" tubing; set @3342' with SN @3255'. Turned well to Sid Richardson sales @9 AM 10/12/97. Final Report				
SIGNATURE WILLIAM	www.	TILE Regulatory		
TYPE OR PRINT NAME	Debra Harris	 	TELEPHONE NO. (281) 469-9	7004
(This space for State Use)OFIGINAL SIGNAL DISTRICT	I SUPERVISOR	ITLE	DATE	•
CONDITIONS OF APPROVAL, IF ANY:				