+Submit 3 Cor es to Appropriate

State of New Mexico

Form C 103

Energy, Minerals and Natural Resources Department Revised 1-1-89 District Office DISTRICT I OIL CONSERVATION DIVISION WELL API NO. P.O. Box 1980, Hobbs, NM S8240 P.O. Box 2088 30 025 04721 DISTRICT II Santa Fe, New Mexico 87504-2088 5. Indicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 STATE FEE DISTRICT III 6. State Oil& Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 B1533 1/2 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well \bowtie State C-20 Well OTHER 2. Name of Operator 8. Well No. Conoco Inc. 3. Address of Operator 9. Pool name or Wildcat 10 Desta Dr. Ste 100W, Midland, Tx., 79705-4500 Eumont Yates 7 Rvrs Queen 4. Well Location 660 South 1980 West Feet From The Line and Feet From The Line Section 20 Township **NMPM** County **21S** Range 36E Lea 10. Elevation (Show whether DF, RKB. RT, GR, etc.) Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. **NOTICE OF INTENTION TO:** SUBSEQUENT REPORT OF: PLUG AND ABANDON PERFORM REMEDIAL WORK REMEDIAL WORK ALTERING CASING **CHANGE PLANS TEMPORARILY ABANDON** COMMENCE DRILLING OPNS. **PLUG AND ABANDONMENT PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHERPut well back on prod, generalijels & perforate OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 4-7-97: Drilled out cement from 106 to 248'. 4-8-97: Finish in hole to PBTD @ 3784'. 4-9-97: Perforated Lower Eumont w/l spf from 3436 - 3741'. Set Packer @ 3416'. 4-10-97: Acidized with 750 gals 7.5% HCL-NEFE, 93 bbls 70 quality CO2 foam pad, 377 bbls 60-55 Quality CO2 foam, ramping 108,000# 12/20 ottawa. Perforate Upper Eumont wl spf from 3103 - 3398'. Acidize - 220 gals pre-pad, 129 bbls 70 Quality CO2 foam pad, 588 bbls 60-55 Quality CO2 foam with 174,000# 12/20 Ottawa Sand. 4-17-97: Cleaned out hole, sand - ran tubing with seating nipple @ 3719'. 4-18-97: Installed separator & meter run, well put on production.

e to the best of my knowledge and belief. I hereby certify that the information abo Regulatory Agent $\frac{5-20-97}{}$ TYPE OR PRINT NAME Ann E. Ritchie TELEPHONE NO. 915 684-6381

- TITLE -

(this space for State Use)

APPROVED BY _

Orig. Signed by Paul Kautz Geologist

MAY 2 2 1997