

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

100-100000-000

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON Setting Liner (Other) & Acidizing	X

April 4, 1955
(Date)

Hobbs, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Continental Oil Company
(Company or Operator)

State 0-20
(Lease)

(Contractor), Well No. 8 in the NW 1/4 SW 1/4 of Sec. 20

T. 21S, R. 36E, NMPM, Emine Pool, Lea County.

The Dates of this work were as follows: 2-18-55 to 2-25-55

Notice of intention to do the work (was) (XXXX) submitted on Form C-102 on Feb. 17, 1955
(Cross out incorrect words)

and approval of the proposed plan (was) (XXXX) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The subject well was pumping approximately 500 bbls. water per day, no oil. 5 1/2" casing set at 3835'. Open hole section 3835-3968'. Grayburg pay 3860-3968'.

The following work was performed: washed over fish to 3855'. Ran tapered mill, failed to get fish. Ran 4 11/16" overshot, stopped 30' from top of fish. Ran 4 3/4" bit, reamed to top of fish. Ran tapered tap, recovered lower part of packer and 107' of 2 1/2" tail pipe. Reamed hole to T.D. Set 166' of 4" OD liner on bottom. Cemented with 75 sacks cement. Drilled out cement to 3966'. Perforated liner with 4 holes per foot from 3929-3959'. Treated through liner perforations with 500 gallons 15% acid.

After workover, well pumped 15 bbls. oil, 77 bbls. water in 24 hours.

ILLEGIBLE

Witnessed by (Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

J. G. Stanley
(Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: [Signature]

Position: District Superintendent

Representing: Continental Oil Company

Address: Box 427, Hobbs, New Mexico