

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

SEP 20 PM 3:41

Submit this notice in TRIPPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) <b>Repr. Csg. Leak X</b>		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico

September 16, 1955

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the J. F. Janda "A"

Gulf Oil Corporation  
(Company or Operator)

Well No. 1 in P  
(Unit)

SE  $\frac{1}{4}$  SE  $\frac{1}{4}$  of Sec. 20, T. 21-S, R. 36-E, NMPM., Eunice Pool  
(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Since a number of leaks have been discovered in the 5-1/2" oil string it is proposed to run a 4-1/2" casing liner as follows:

1. Pull rods and tubing.
2. Run gauge ring to 3800'. Set Baker Model D production packer at 3790'.
3. Run 4-1/2" OD Hydrill Flush Joint liner assembly as follows:  
2, Baker Multi V seal nipples with bottom and ball plugged; 1, 2" x 10' perforated nipple; 2, Baker Multi V seal nipples; 1, locator sub; 1, 2-3/8" x 4-1/2" swage nipple; 4-1/2" OD Hydrill Flush Joint casing to surface.
4. Engage bottom set of seal nipples in packer and circulate heavy mud to surface. Displace mud in casing with water. Then lower 4-1/2" casing until top seal nipples are engaged in Baker packer.
5. Rerun tubing and rods. Return well to production.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title..... Engineer District I

Gulf Oil Corporation  
Company or Operator

By.....

Position..... Area Supt. of Prod.  
Send Communications regarding well to:

Name..... Gulf Oil Corporation

Address..... Box 2167, Hobbs, N. M.