## NEW MEXICO STATE LAND OFFICE SANTA FE, NEW MEXICO

## DEPARTMENT OF THE STATE GEOLOGIST NOTICE OF TEST OF WATER SHUT-OFF

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector at least five days before the test. It is desirable that a representative of the Department of the State Geologist witness the water shut-off before drilling into the productive sand whenever possible. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to sender. Submit this notice in duplicate.

E. H. Wells   State Geologist, Santa Fe, New Mexico.   ar Sir: You are hereby notified that we intend to test the shut- ell No. 1 in SE/4 of Sec. 20   M. P. M. Eunice   M. P. M. Eunice   Oil Field   August 6, 19 35 52" 17 Ib. c   rmation at a depth of 3848 feet on.   300 sacks of El Toro 011 Well   The method used in placing the cement was as follows:   Halliburton pumping plug method.   Fluid level will be bailed to a depth of hours before your inspection.   Adjacent property owners have been notified as follows:   Continental 011 Co., Humble 0 & R Co.,   Additional information:   Hydrau lic pressure of 1200# will   before and after drilling plug.	T. <b>21-9</b> , R. <b>36-E</b> Loa County, asing was cemented in <b>Line</b> August 3 19 35 cement were used.
Santa Fe, New Mexico. ar Sir: You are hereby notified that we intend to test the shut- ell No. 1 in SE/4 of Sec. 20 M. P. M., Eunice Oil Field August 6, 19 35 5 <sup>2</sup> 17 Ib c rmation at a depth of 3848 feet on 300 sacks of El Toro Oil Well The method used in placing the cement was as follows: Halliburton pumping plug method. Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as follows: Continental Oil Co., Humble O & R Co., Additional information: Hydraulic pressure of 1200# will before and after drilling plug.	T. <b>21-9</b> , R. <b>36-E</b> Loa County, asing was cemented in <b>Line</b> August 3 19 35 cement were used.
You are hereby notified that we intend to test the shut- ell No in SE/4 of Sec. 20 M. P. M., Oil Field August 6, 19 35 54" 17 lb. c rmation at a depth of 3848 feet on 300 sacks of Feet on 300 sacks of Toro 011 Well The method used in placing the cement was as follows: Halliburton pumping plug method. Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as follows: Contimental 011 Co., Humble 0 & R Co., Additional information: Hydraulic pressure of 1200# will before and after drilling plug.	T. <b>21-9</b> , R. <b>36-E</b> Loa County, asing was cemented in <b>Line</b> August 3 19 35 cement were used.
M. P. M., Eunice Oil Field   August 6, 19 35 53" 17 b. c   rmation at a depth of 3848 feet on.   300 sacks of El Toro Oil Well   The method used in placing the cement was as follows: Halliburton pumping plug method.   Fluid level will be bailed to a depth of hours before your inspection.   Adjacent property owners have been notified as follows:   Continental Oil Co., Humble 0 & R Co.,   Additional information:   Hydrau lic pressure of 1200# will   before ami after drilling plug.	Lea County, asing was cemented in Line August 3 19 35 cement were used.
August 6, 19.35.52" 17 lb. c   rmation at a depth of 3848 feet on   300 sacks of El Toro Oil Well   The method used in placing the cement was as follows: Halliburton pumping plug method.   Fluid level will be bailed to a depth of hours before your inspection.   Adjacent property owners have been notified as follows:   Continental Oil Co., Humble O & R Co.,   Additional information:   Hydrau lic pressure of 1200# will   before and after drilling plug.	asing was cemented in Line August 3 19 35 cement were used.
rmation at a depth of	cement were used.
300 sacks of El Toro Oil Well   The method used in placing the cement was as follows: Halliburton pumping plug method.   Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as follows:   Continental Oil Co., Humble O & R Co., Additional information: Hydraulic pressure of 1200# will   before and after drilling plug. 19 Sincere	cement were used.
The method used in placing the cement was as follows: Halliburton pumping plug method. Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as follows: Contimental Oil Co., Humble O & R Co., Additional information: Hydraulic pressure of 1200# will before and after drilling plug. Sincere	feet and left undisturbed for at least
Halliburton pumping plug method. Fluid level will be bailed to a depth of	
Fluid level will be bailed to a depth of hours before your inspection. Adjacent property owners have been notified as follows: Continental Oil Co., Humble O & R Co., Additional information: Hydraulic pressure of 1800# will before and after drilling plug.	
hours before your inspection. Adjacent property owners have been notified as follows: Continental Oil Co., Humble O & R Co., Additional information: Hydraulic pressure of 1200# will before and after drilling plug. Sincere	
Adjacent property owners have been notified as follows: Continental Oil Co., Humble O & R Co., Additional information: Hydraulic pressure of 1200# will before and after drilling plug. Sincere	Atlantic Oil Prod. Co.,
Continental Oil Co., Humble O & R Co., Additional information: Hydraulic pressure of 1200# will before and after drilling plug.	
Additional information: <b>Hydrau lic pressure of 1200# will</b> before and after drilling plug. Adde a digitation oproved	
oproved 19	be applied to 5%" casing
· ^	ly yours,
	HE CALIFORNIA COMPANY
-	Company or Operator.
	R. Norris & Starris
Position	1171 TAB T' (116) TYP
	munication regarding well to
Address State Geologican Oil and Gas Inspector.	