Form SG 106

NEW MEXICO STATE LAND OFFICE

OFFICE OF THE STATE GEOLO

SANTA FE, NEW MEXICO



MISCELLANEOUS REPORTS ON WELLS

Submit this report in duplicate to the State Geologist or proper Oil and Gas Inspector within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of weier shut-off, result of abandonment of well, and other important operations, even though the work was witnessed by the State Geologist or Oil and Gas Inspector. Reports on minor operations need not be signed and sworn to before a notary public, but such operations should be witnessed by an Oil and Gas inspector if possible.

indicate nature of report by checking below.				
REPORT ON BEGINNING DRIRLLING OPERATIONS	X	REPORT ON DEEPENI	NG WELL	
REPORT ON RESULT OF SHOOTING WELL		REPORT ON PULLING ALTERING CASING	OR OTHERWISE	
REPORT ON RESULT OF TEST OF WATER SHUT-OFF		REPORT ON REPAIRIN	IG WELL	
REPORT ON RESULT OF ABANDONMENT OF WELL				
	Mł	Aland. Maras	July 12.	1935

Midland, Texas July 12, Place Date

Mr E. H. Wells State Geologist,

Santa Fe, N. Mex.

 Following is a report on the work done and the results obtained under the heading noted above at the

 The Cal 1fornia Co. N.M. State 2

 Well No

 Company or Operator

 Company or Operator

 SE/4
 of Sec
 20
 , T
 21-S
 , R
 36-E
 N. M. P. M.,

 Leas
 County.

 Eunice
 Oil Field,
 County.

 The dates of this work were as follows:
 6-21-35 to July 4, 1935
 1935

 Notice of intention to do the work was (warned) sumbitted on Form SG
 101
 on

 June 21,
 19 35, and approval of the proposed plan was (warned) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

June 21 to June 30, 1935, digging cellar and pits, and rigging up. Spudded at 1 PM June 30, 1935. Drill ed 17-1/2" hole to 64'. Landed and cemented 45' of 13-3/8" casing (54.5#, 8 thread, S.H., Seamless) at 62' using 25 sacks cement around collar and 50 sacks to cement casing, Halliburton process. Drilled ahead with 11" Hughes drag bit and July 3, 1935, had drilled to total depth of 670 feet.

Subscribed and sworn to before me this	I hereby swear or affirm that the information given above is true and correct.
12th day of July ,19 55	
man municul	Position Supt. DrIg., Const. & Mts.
Notary Public	Representing THE CAL IF OHN IA COMPANY Company or Operator
My Commission expires May 31 1937	Address Drawer "R", Midland, Texas
Remarks: Above casing shown on SG	101 as 12-1/2".
markson I have	Supt. D.C.M.
Head, the	Name Title

on one was in the test to the poly of

e ya konst Minaini andi ka kantata

AND REPAIRS FOR T

ATTELAT STRUCT L MERCARDENA

part de la contra d En la contra de la c and the state of the

- 読む かえる ディー・キャガン かいきやく 読み

 A static strategy of the static andar Antonio (11) antonio 1.11 . *----

ć i

· · · · · •__ - ^{- 1} **,** . •

ę

and a second A second secon a da antiand the provide the second Gatessian $= \frac{1}{2} \left[\frac{1}{2}$ TE TO ROUGELE

and the second secon - • • • • • • •

and the second sec

• • • • · · ·