

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NEEDS OFFICE 000

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) <b>Acid Frac Treat</b>	<b>X</b>	NOTICE OF INTENTION (OTHER) <b>Repr. Csg. Lk.</b>	<b>X</b>

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

**Hobbs, New Mexico**  
(Place)

**April 4, 1955**  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the **Arnett Ramsay "C"**  
**Gulf Oil Corporation** Well No. **11** in **I**  
(Company or Operator) (Unit)  
**NE**  $\frac{1}{4}$  **SE**  $\frac{1}{4}$  of Sec. **21**, T. **21-S**, R. **36-E**, NMPM, **Eunice** Pool  
(40-acre Subdivision)  
**Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Propose to treat open hole formation from 3790-3890' with 5000 gallons acid frac, 1# sand per gallon. If tests indicate further exploitation of the well is warranted, propose to repair casing leak in 5-1/2" casing as follows:

1. Set magnesium bridge plug on wire line in 5-1/2" casing at approx. 3770'.  
Dump 1 sack cement on top.
2. Run HRC tool and locate leak interval.
3. Attempt to establish circulation out hole to surface thru 5-1/2" - 7-5/8" annulus.
4. Set mag. retainer above hole. Cement thru retainer with sufficient volume to circulate to surface.
5. Wait on cement.
6. Pressure test casing above retainer. If OK, drill out cement and retainer.
7. Pressure test casing above bridge plug. If OK, drill out bridge plug and clean hole.
8. Return well to production.

Approved \_\_\_\_\_, 19\_\_\_\_  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By **J. J. Stanley**

Title \_\_\_\_\_

**Gulf Oil Corporation**

Company or Operator

By **E. F. Taylor**

Position **Area Supt. of Prod.**

Send Communications regarding well to:

Name **Gulf Oil Corporation**

Address **Box 2167, Hobbs, N. M.**