NI MEXICO OIL CONSERVATION C MISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

NOTICE OF INTENTION TO TEST CASING SHUT-OFF 5	1/2"	NOTICE OF INTENTION TO SHOO	T OR
NOTICE OF INTENTION TO CHANGE PLANS	1/2"	NOTICE OF INTENTION TO PULI	
NOTICE OF INTENTION TO REPAIR WELL		OTHERWISE ALTER CASING	
		NOTICE OF INTENTION TO PLUG	WELL
NOTICE OF INTENTION TO DEEPEN WELL	li		
I		New Mexico May 19th 1937	•
OIL CONSERVATION COMMISSION,	Pi	pice	Date
Santa Fe, New Mexico.			
Gentlemen:			
Following is a notice of intention to do certain work a	ıs descri	bed below at the	
df Oil Corpn - Gypsy Division - Arno	ott Ra	msay "C" #14 _{Well No.} #14	SW/4
of Sec. 21 Company or Operator 21S R. 36E		Lease M. P. M., Eunice	
County.	,.N.	M. P. W.,	Fiel
		OSED PLAN OF WORK	
e Halliburton Cementing process. (55	joint	8 5 1/2" 17# 10thd new Sor) sacks cement th Chester la
y 19th 1937 the 5 1/2 " casing was centered to Halliburton Cementing process. (55 sel casing on bottom, 80 joints 5 1/2" opose to drill plug and test on May 21	joint;	in Lime at 3780° with 150 s 5 1/2° 17# 10thd new Soulothd new National SS casi) sacks cement
e Halliburton Cementing process. (55 eel casing on bottom, 80 joints 5 1/2"	joint;	in Lime at 3780° with 150 s 5 1/2° 17# 10thd new Soulothd new National SS casi	O sacks cement ith Chester la ing Grade "C"
e Halliburton Cementing process. (55 eel casing on bottom, 80 joints 5 1/2"	joint;	in Lime at 3780° with 150 s 5 1/2° 17# 10thd new Soulothd new National SS casi	o sacks cement ith Chester la ing Grade "C"
e Halliburton Cementing process. (55 seel casing on bottom, 80 joints 5 1/2" opose to drill plug and test on May 21 pproved	joint; 17# : .st 19:	in Lime at 3780° with 150 s 5 1/2° 17# 10thd new Soulothd new National SS casi 37. Gulf Oil Corpn - Gypsy Di Company or Operator	o sacks cement ith Chester la ing Grade "C"
e Halliburton Cementing process. (55 seel casing on bottom, 80 joints 5 1/2" opose to drill plug and test on May 21 pproved	joint; 17# : .st 19:	in Lime at 3780° with 150 s 5 1/2° 17# 10thd new Soulothd new National SS casis 37. Gulf Oil Corpn - Gypsy Di Company or Operator	o sacks cement ith Chester la ing Grade "C"
e Halliburton Cementing process. (55 seel casing on bottom, 80 joints 5 1/2" opose to drill plug and test on May 21 pproved	joint; 17# : .st 19:	in Lime at 3780° with 150 s 5 1/2" 17# 10thd new Soulothd new National SS casi 37. Gulf Oil Corpn - Gypsy Di Company or Operator Company or Opera	o sacks cement ith Chester la ing Grade "C"
e Halliburton Cementing process. (55 seel casing on bottom, 80 joints 5 1/2" opose to drill plug and test on May 21 pproved	joint; 17# : .st 19:	in Lime at 3780° with 150 s 5 1/2° 17# 10thd new Soul 10thd new National SS casi 37. Gulf Oil Corpn - Gypsy Di Company or Operator Company or Operator Company or Operator Send communications ragarding	sacks cement the Chester 1 ing Grade "C"
pproved 193*	joint; 17# : .st 19:	in Lime at 3780° with 150 s 5 1/2° 17# 10thd new Soul 10thd new National SS casi 37. Gulf Oil Corpn - Gypsy Di Company or Operator Company or Operator Company or Operator Send communications ragarding	sacks cemer ith Chester I ing Grade "C"