Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, instructions in the Rules and Regulations of the Commission. See additional

	Indicate Nature of Report by Checking B	selow
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPAIRING WELL  REPORT ON (Other)
		INSTALL PUMP FOULP. X
	June 20 Toro	
Foliani	(Date)	Hobbs, New Mexico
rollowing is a report on the work	done and the results obtained under the heading i	10trd above of the
Gulf Oil Corporation	erator)	
(Company or Ope	erator)	Harry Leonard "A"
(Contractor	Well No.	. An -
21-S , R 36-E NMPM E	mice Pool,	14 of Sec. 22
, == 0.21,	Pool,	
he Dates of this work were as folows:	June 23-28, 1953	Coun
ntice of intention .		
office of intention to do the work (was)	(vaccing submitted on Form C-102 on Mark	20
d approval of the proposed plan (was)	(was not) obtained.	Cross out incorrect words) 19.5
	(was not) obtained.	
TATOM A TO		
DETAIL:	ED ACCOUNT OF WORK DONE AND RESUL	TS OBTAINED
NUDUCLIERO CONSTANTAN	ED ACCOUNT OF WORK DONE AND RESUL	
AUGUALLER CONST AC YOU AS		
tubing. Tubing set at 38	D Pumping Unit w/10 HP Electric M 78, seating nipple 3861; Pens	otor. Ran 122 Jts. 38731
tubing. Tubing set at 38	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Peri.	otor. Ran 122 Jts. 3873:
tubing. Tubing set at 38 Pumped on Oil Conservation tubing in 24 hours 12	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.	otor. Ran 122 Jts. 3873:
tubing. Tubing set at 38 Pumped on Oil Conservation tubing in 24 hours 12	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.	otor. Ran 122 Jts. 3873:
tubing. Tubing set at 38 Pumped on Oil Conservation ubing in 24 hours 12	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.	otor. Ran 122 Jts. 3873:
tubing. Tubing set at 38	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.	otor. Ran 122 Jts. 3873:
tubing. Tubing set at 38 Pumped on Oil Conservation ubing in 24 hours 12	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.	otor. Ran 122 Jts. 3873:
tubing. Tubing set at 38 Pumped on Oil Conservation tubing in 24 hours 12	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.	otor. Ran 122 Jts. 3873:
tubing. Tubing set at 38 Pumped on Oil Conservation tubing in 24 hours 12	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.	otor. Ran 122 Jts. 3873:
tubing. Tubing set at 38 Pumped on Oil Conservation tubing in 24 hours 12	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.	otor. Ran 122 Jts. 3873:
tubing. Tubing set at 38 Pumped on Oil Conservation bubing in 24 hours 12 -	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.	otor. Ran 122 Jts. 3873:
tubing. Tubing set at 38 Pumped on Oil Conservation tubing in 24 hours, 12 x 14 Milowable after equi ment	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf. : In Commission test 38 bbls oil 44 h 48 spm. Allowable before equipment replacement 38 BOPD.	otor. Ran 122 Jts. 3873:
tubing. Tubing set at 38 Pumped on Oil Conservation tubing in 24 hours, 12 x 14 Milowable after equi ment	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf. : In Commission test 38 bbls oil 44 h 48 spm. Allowable before equipment replacement 38 BOPD.	otor. Ran 122 Jts. 3873' 3863-67. Ran pump & rods. obls water thru 2-3/8" it replacement 8 BOPD
tubing. Tubing set at 38 Pumped on Oil Conservation tubing in 24 hours, 12 x Lullowable after equi ment	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.	otor. Ran 122 Jts. 3873' 3863-67. Ran pump & rods. obls water thru 2-3/8" it replacement 8 BOPD
tubing. Tubing set at 38 Pumped on Oil Conservation tubing in 24 hours, 12 x Lullowable after equi ment ment measured by G. O. Paysinger (Name)	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.  Commission test 38 bbls oil 44 h 8 spm. Allowable before equipment replacement 38 BOPD.  Gulf Oil Corporation (Company)	otor. Ran 122 Jts. 3873' 3863-67. Kan pump & rods.  oblis water thru 2-3/8" at replacement 8 BOPD
tubing. Tubing set at 38 Pumped on Oil Conservation tubing in 24 hours, 12 x Lullowable after equi ment	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.  Commission test 36 bbls oil 44 h 8 spm. Allowable before equipment replacement 38 HOPD.  Gulf Oil Corporation (Company)  I hereby certify that the	otor. Ran 122 Jts. 3873' 3863-67. Ran pump & rods.  obls water thru 2-3/8" at replacement 8 BOPD  Field Foreman
tubing. Tubing set at 38 Pumped on Oil Conservation tubing in 24 hours, 12 x Lullowable after equi ment ment measured by G. O. Paysinger (Name)	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.  Commission test 36 bbls oil 44 h 8 spm. Allowable before equipment replacement 38 HOPD.  Gulf Oil Corporation (Company)  I hereby certify that th to the best of my know	otor. Ran 122 Jts. 3873' 3863-67. Ran pump & rods.  obls water thru 2-3/8" at replacement 8 BOPD  Field Foreman
tubing. Tubing set at 38 Pumped on Oil Conservation tubing in 24 hours, 12 x Lullowable after equi ment ment measured by G. O. Paysinger (Name)	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.  Commission test 38 bbls oil 44 h 8 spm. Allowable before equipment replacement 38 EOPD.  Gulf Oil Corporation (Company)  I hereby certify that th to the best of my known  Name.  Name.	Stor. Ran 122 Jts. 3873' 3863-67. Ran pump & rods.  Oblis water thru 2-3/8" It replacement 8 BOPD  Field Foreman  (Title)  e information given above is true and complete ledge.
tubing. Tubing set at 38 Pumped on Oil Conservation tubing in 24 hours, 12 x Lubing in 24 hours, 12 x Lubing in after equi ment	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.  Commission test 38 bbls oil 44 h 8 spm. Allowable before equipment replacement 38 EOPD.  Gulf Oil Corporation (Company)  I hereby certify that th to the best of my known Name.  Position Asst. Area	Field Foreman  e information given above is true and complete  ledge.
tubing. Tubing set at 38 Pumped on Oil Conservation tubing in 24 hours, 12 x Lullowable after equi ment ment measured by G. O. Paysinger (Name)	D Pumping Unit w/10 HP Electric M 78', seating nipple 3861', Perf.  Commission test 38 bbls oil 44 h 8 spm. Allowable before equipment replacement 38 EOPD.  Gulf Oil Corporation (Company)  I hereby certify that th to the best of my known Name.  Position Asst. Area	Stor. Ran 122 Jts. 3873' 3863-67. Ran pump & rods.  Oblis water thru 2-3/8" It replacement 8 BOPD  Field Foreman  (Title)  e information given above is true and complete ledge.