

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-025-04758
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name: Eunice Monument South Unit
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐	8. Well No. 433	
2. Name of Operator Chevron USA, Inc.	9. Pool name or Wildcat Eunice Monument, Grayburg, SA	
3. Address of Operator 15 Smith Rd., Midland, Texas 79705		
4. Well Location Unit Letter <u>A</u> : <u>660</u> feet from the <u>North</u> line and <u>660</u> feet from the <u>East</u> line Section <u>22</u> Township <u>21-S</u> Range <u>36-E</u> NMPM County <u>Lea</u>		
10. Elevation (Show whether DR, RKB, RT, GR, etc.)		


11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒ TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐ OTHER: ☐	SUBSEQUENT REPORT OF: REMEDIAL WORK ☐ ALTERING CASING ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐ CASING TEST AND CEMENT JOB ☐ OTHER: ☐
---	--

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Notify OCD 24 hrs prior to MI & RU.
2. RIH Tag 5 1/2" CIBP @ 3688' (Grayburg) Spot 25 Sx plug 3688'-3450' (Queen) WOC Tag.
3. Displace hole w/MLF, 9.5# Brine w/25# Gel P/BBL.
4. Spot 25 Sx plug 2600'-2400' (B-Salt) WOC Tag.
5. Perf 4 holes @ 1500' Sqz 75 Sx plug 1500'-1200' (7 5/8" Shoe, B-Salt) WOC Tag.
6. Perf 4 holes @ 250', Sqz 50 Sx plug 250'-Surf 5 1/2" (13 3/8" Shoe, Surf) WOC Tag.
7. Install dry hole marker.

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE G.R. Bledsoe TITLE HES Specialist DATE 6/17/2002
Type or print name G.R. Bledsoe Telephone No. 915.687.7153
(This space for State use)

APPROVED BY GARY WITTEK DATE JUN 21 2002
Conditions of approval, if any: OC FIELD REPRESENTATIVE II/STAFF MANAGER

PLUGGING & ABANDONMENT WORKSHEET

(3 STRING CSNG)

OPERATOR CHEVRO

USA Inc.

LEASE NAME EUNICE Monument SOUTH UNIT

WELL # 433

SECT 22

TWN 21-S

RNG 36-E

FROM 660

N/S L 660

E/W L

TD 3986

FORMATION @ TD

PBTD

FORMATION @ PBTD GRAYBURG

13 3/8
@ 34'
TOC SURF

7 5/8
@ 1430
TOC SURF

5 1/2
@ 3738
TOC 1841

TD 3986

	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	13 3/8	34'	SURF	Circ
INTMED 1	7 5/8	1430	SURF	Circ
INTMED 2				
PROD	5 1/2	3738	1841	CALC

	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1					
LINER 2					

	CUT & PULL	TOP - BOTTOM
INTMED 1	PERFS	
INTMED 2	OPENHOLE	3738 - 3986
PROD		

*REQUIRED PLUGS DISTRICT

	PLUG	TYPE PLUG	SACKS CEMENT	DEPTH
RUSTLER (ANHYD)	1	QUEEN	25	3688
YATES	2	B-SALT	25	2600
QUEEN	3	7 5/8 S	75	1500
GRAYBURG	4	13 3/8 S	50	250
SAN ANDRES				
CAPITAN REEF				
DELAWARE				
BELL CANYON				
CHERRY CANYON				
BRUSHY CANYON				
BONE SPRING				
GLORIETA				
BLINBRY				
TUBB				
DRINKARD				
ABO				
WC				
PENN				
STRAWN				
ATOKA				
MORROW				
MISS				
DEVONIAN				

