

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<b>XX</b>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

September 3, 1952  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Harry Leonard "A"

Gulf Oil Corporation

(Company or Operator)

Well No. 4 in G

(Unit)

SW  $\frac{1}{4}$  NE  $\frac{1}{4}$  of Sec. 22, T. 21-S, R. 36-E, NMPM., Bunice Pool

(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Propose to Plug and Abandon, procedure as follows: 1. Load hole with water and pull tubing. - 2. Run tubing with Baker Model K cast iron cement retainer. Set retainer at 3775' and squeeze with 23 sacks cement (20 sacks below retainer and 3 above). - 3. Displace water with heavy mud and pull tubing. - 4. Shoot and pull 5 $\frac{1}{2}$ " casing. - 5. Spot cement plug from 1485' to 1435' with 20 sacks cement. - 6. Shoot and pull 7-5/8" casing. - 7. Spot cement plug from 40' to surface with 35 sacks of cement. - 8. Install a 4" steel pipe marker to extend above ground level a minimum of 4'.

Approved \_\_\_\_\_, 19\_\_\_\_

Except as follows: If 7 5/8" casing recovered cement solid from top 7 5/8 or top of Red Beds, whichever is higher, to surface

Approved  
OIL CONSERVATION COMMISSION

By R. A. Blynn

Title \_\_\_\_\_

Gulf Oil Corporation

(Company or Operator)

By Chas. Taylor

Position Area Prod. Supt.

Send Communications regarding well to:

Name Gulf Oil Corporation

Address Box 2167, Hobbs, New Mexico