

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

**DUPLICATE**

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS

REPORT ON REPAIRING WELL

REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL

REPORT ON PULLING OR OTHERWISE ALTERING CASING

REPORT ON RESULT OF TEST OF CASING SHUT-OFF

REPORT ON DEEPENING WELL

REPORT ON RESULT OF PLUGGING OF WELL

X

Midland, Texas, September 1, 1942

Place

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the  
**Humble Oil & Refining Company N. M. State "G"** Well No. **3** in theCompany or Operator  
**NE/4 of SE/4**of Sec. **26**

Lease

**21-S**

, R.

**36-E**

, N. M. P. M.,

**Eunice**

Field,

**Lea**

County.

The dates of this work were as follows: **August 29, 30, 31, 1942**Notice of intention to do the work was (was not) submitted on Form C-102 on **Aug. 29** 19 **42**  
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Cemented hole from 3960' to 3600' with 35 sacks Lone Star cement. Plugged below 7-5/8" casing 1400' to 1300' with 40 sacks Lone Star cement. Filled hole with heavy mud-laden fluid. Shot 7-5/8" casing at 536', 400', 305' and 250'. Recovered 240.7' of 7-5/8" casing, leaving 1121.84' of 7-5/8" casing in hole. Plugged hole 214' to 164' with 25 sacks Lone Star cement and filled hole with heavy mud-laden fluid. Plugged top of hole with 10 sacks Lone Star cement and set regulation marker in accordance with New Mexico Oil Conservation Commission regulations. Left 201.18' of 10-3/4" casing in hole.

No witness

Witnessed by \_\_\_\_\_ Name \_\_\_\_\_ Company \_\_\_\_\_ Title \_\_\_\_\_

Subscribed and sworn before me this **1st**day of **September**, 19 **42****Wesley Lee Ferguson**

Notary Public

My commission expires **6-1-43**

I hereby swear or affirm that the information given above is true and correct.

Name **W. H. Hume**Position **Division Superintendent**Representing **Humble Oil & Refining Company**

Company or Operator

Address **Box 1600, Midland, Texas**

Remarks:

Name

OIL &amp; GAS INSPECTOR

Title