

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) To Recomplete	X	NOTICE OF INTENTION (OTHER) To Fracture	X

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

November 11, 1955
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the **New Mexico State G**

Humble Oil & Refining Company

(Company or Operator)

Well No. **4** in **G**
(Unit)

SW $\frac{1}{4}$ **NE** $\frac{1}{4}$ of Sec. **26**, T. **21S**, R. **36E**, NMPM., **Arrowhead** Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

The purpose of this work is to recomplete lower in the Queen pay as follows:

1. Drill out bridge plug at 3774.
 2. Set packer on 4-inch tubing at approximately 3770 and fracture the perforated section from 3784 to 3860 with 20,000 gals of refined oil and 30,000 lbs of sand.
 3. Swab and test fractured zone. Complete well to produce from 3784 to 3860.
- In the event a commercial oil well is not obtained:
4. Set bridge plug at approximately 3770. Dump cement on top.
 5. Fracture the perforated sections from 3580 to 3612 and 3644 to 3754 with 20,000 gals of refined oil and 30,000 lbs of sand.
 6. Swab and test. Complete well.

Current production test: $1\frac{1}{4}$ " choke, TP 50#, 4.19 BOPD, 16% water, GOR 31,551, producing through perforations from 3580 to 3612 and 3644 to 3754.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

Humble Oil & Refining Company

Company or Operator

By *R. M. Gillette*

Position **Agent**

Send Communications regarding well to:

Name **R. M. Gillette**

Address **Box 2347, Hobbs, New Mexico**
epj