

RECORD OF DRILL-STEM AND SPECIAL TESTS

IF DRILL-STEM OR OTHER SPECIAL TESTS OR DEVIATION SURVEYS WERE MADE, SUBMIT REPORT ON SEPARATE SHEET AND ATTACH HERETO

No Drill Stem Tests

TOOLS USED

ROTARY TOOLS WERE USED FROM 0 FEET TO 3880 FEET, AND FROM = FEET TO = FEET.
CABLE TOOLS WERE USED FROM = FEET TO = FEET, AND FROM = FEET TO = FEET.

PRODUCTION

PUT TO PRODUCING June 1, 1958

OIL WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS 87 BARRELS OF LIQUID OF WHICH 100 % WAS OIL, = % WAS EMULSION, = % WATER, AND = % WAS SEDIMENT. A.P.I. GRAVITY 35.8

GAS WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS = M.C.F. PLUS = BARRELS OF LIQUID HYDROCARBON. SHUT IN PRESSURE = LBS.

LENGTH OF TIME SHUT IN =

PLEASE INDICATE BELOW FORMATION TOPS (In Conformance With Geographical Section Of State):

SOUTHEASTERN NEW MEXICO

NORTHWESTERN NEW MEXICO

T. ANHY 1422	T. DEVONIAN	T. OJO ALAMO
T. SALT 1510	T. SILURIAN	T. KIRTLAND-FRUITLAND
B. SALT 2722	T. MONTOKA	T. FARMINGTON
T. YATES 2935	T. SIMPSON	T. PICTURED CLIFFS
T. 7 RIVERS 3215	T. McKEE	T. MENELEE
T. QUEEN 3576	T. ELLENBURGER	T. POINT LOOKOUT
T. GRAYBURG 3830	T. GR. WASH	T. MANCOS
T. SAN ANDRES	T. GRANITE	T. DAKOTA
T. GLORIETA	T.	T. MORRISON
T. DRINKARD	T.	T. PENN
T. TUBBS	T.	T.
T. ABO	T.	T.
T. PENN	T.	T.
T. MISS	T.	T.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	1422	1422	Redbeds				
1422	1510	88	Anhydrite				
1510	2935	1425	Salt & anhydrite				
2935	3215	280	Shale, salt, anhydrite				
3215	3576	361	Dolomite & anhydrite				
3576	3830	254	Sandstone, anhydrite, dolomite, & shale				
3830	3880	50	Dolomite & anhydrite				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEREBY SWEAR OR AFFIRM THAT THE INFORMATION GIVEN HERewith IS A COMPLETE AND CORRECT RECORD OF THE WELL AND ALL WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

6-18-58

COMPANY OR OPERATOR Humble Oil & Refining Company

ADDRESS P. O. Box 2347 - Hobbs, New Mexico

NAME

POSITION OR TITLE

Agent