

RECORD OF DRILLING AND SPECIAL TESTS

IF DRILL-STEM OR OTHER SPECIAL TESTS OR DEVIATION SURVEYS WERE MADE, SUBMIT REPORT ON SEPARATE SHEET AND ATTACH HERETO

TOOLS USED

ROTARY TOOLS WERE USED FROM 0 FEET TO 3390 FEET, AND FROM FEET TO FEET.
CABLE TOOLS WERE USED FROM FEET TO FEET, AND FROM FEET TO FEET.

PRODUCTION

PUT TO PRODUCING December 31, 1938.
OIL WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS 23 BARRELS OF LIQUID OF WHICH 87% WAS OIL; 13% WAS EMULSION; 13% WAS WATER; AND 13% WAS SEDIMENT. A.P.I. GRAVITY 36.3

GAS WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS _____ MCF. PER DAY.
BARRELS OF LIQUID HYDROCARBON. SHUT IN PRESSURE _____ LBS.
LENGTH OF TIME SHUT IN _____

PLEASE INDICATE BELOW FORMATION TOPS (In Conformance With Geographical Section Of State):

SOUTHEASTERN NEW MEXICO			NORTHWESTERN NEW MEXICO		
T. ARMY	1395		T. DEVONIAN		
T. SALT	1487		T. SILURIAN		
T. SALT			T. MONTOYA		
T. YATES	2920		T. SIMPSON		
T. 7 RIVERS	3200		T. McKEE		
T. QUEEN	3595		T. ELLENBURGER		
T. GRAYBURG	3820		T. OR. WASH.		
T. SAN ANDRES			T. GRANITE		
T. GLORIETA			T.		
T. DRINKARD			T.		
T. TUBBS			T.		
T. ABO			T.		
T. PENN.			T.		
T. MISS			T.		

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	1395	1395	Redbeds				
1395	1487	92	Anhydrite				
1487	2920	1433	Salt & anhydrite				
2920	3200	280	Shale, sandstone, salt, & anhydrite				
3200	3595	395	Anhydrite, dolomite				
3595	3820	225	Sandstone, dolomite, & anhydrite				
3820	3890	70	Dolomite & anhydrite				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEEDLY SWEAR OR AFFIRM THAT THE INFORMATION GIVEN HEREIN IS A COMPLETE AND CORRECT RECORD OF THE WELL AND ALL WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

January 4, 1939

COMPANY OR OPERATOR Humble Oil & Refining Company ADDRESS Humble Oil & Refining Co., New Mexico
ORIGINAL R. R. ALWORTH POSITION OR TITLE Agent
NAME SIGNED