

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
CONOCO INC.
3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: **660'FNL & 660'FWL**
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input checked="" type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)	<input type="checkbox"/>	<input type="checkbox"/>

5. LEASE
LC-032.099 (6)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
NMFU
8. FARM OR LEASE NAME
Lockhart B-28
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Eumont Yates Seven Rivers Queen
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 28, T-21S, R-36E
12. COUNTY OR PARISH 13. STATE
Lea NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
- CO to 3930'. Spot 56bbls 15% HCL-NE-FE from 3930'-3802'. String shoot Grayburg open hole section. CO to 3930'. Set pkr 3700'. Acidize 3802'-3930' w/ 65 bbls. 15% HCL-NE-FE. Divert w/ 500# 50% rock salt & 50% Benzoic flakes in 350 gals 10 ppg brine. Pmp 65 bbls 15% HCL-NE-FE. Flush w/ 29 bbls. 2% KCL treated water. Swab. Pmp 2 drums chemical mixed in 20 bbls. 2% KCL treated water. G/H w/ MA, SN to 3845' + 6g. Place on production, test.**

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm A. Butterfield TITLE Administrative Supervisor DATE January 15, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

USGS
NMFU4
FILE

*See Instructions on Reverse Side

APPROVED
JAN 19 1981
DISTRICT SUPERVISOR