

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool _____ Formation _____ County _____

Initial _____ Annual _____ Special _____ Date of Test _____

Company _____ Lease _____ Well No. _____

Unit _____ Sec. _____ Twp. _____ Rge. _____ Purchaser _____

Casing _____ Wt. _____ I.D. _____ Set at _____ Perf. _____ To _____

Tubing _____ Wt. _____ I.D. _____ Set at _____ Perf. _____ To _____

Gas Pay: From _____ To _____ L _____ xG _____ -GL _____ Bar.Press. _____

Producing Thru: Casing _____ Tubing _____ Type Well _____

Date of Completion: _____ Packer _____ Single-Bradenhead-G. G. or G.O. Dual _____ Reservoir Temp. _____

OBSERVED DATA

Tested Through (Prover) (Choke) (Meter) _____ Type Taps _____

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI										
1.										
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w P_f}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.							
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.

Gravity of Liquid Hydrocarbons _____ deg.

F_c _____ (1-e^{-s}) _____

Specific Gravity Separator Gas _____

Specific Gravity Flowing Fluid _____

P_c _____ P_c _____

No.	$\frac{P_w}{P_t}$ (psia)	P _t ²	F _c Q	(F _c Q) ²	$\frac{(F_c Q)^2}{(1-e^{-s})}$	P _w ²	P _c ² -P _w ²	Cal. P _w	$\frac{P_w}{P_c}$
1.									
2.									
3.									
4.									
5.									

Absolute Potential: _____ MCFPD; n _____

COMPANY _____

ADDRESS _____

AGENT and TITLE _____

WITNESSED _____

COMPANY _____

REMARKS

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if
flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressibility factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then F_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .

COMPANY	Continental Oil Co.
WELL	Lockhart E-28 No. 6
LOCATION	A Sec. 28-21S-36E
COUNTY	Lea
DATE	11-21-58

