

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Humble Oil & Refining Company

N. M. State B

N. M. State B

Company or Operator

Well No. 6

in SE 1/4

of Sec. 29

T. S. 21 South

R. R-36 East, N. M. P. M., Eunice, N. M.

Field,

Lea

County.

Well is 4620' feet south of the North line and 1320 feet west of the East line of Section 29

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Humble Oil & Refining Company Address Houston, Texas

Drilling commenced 11/21 1935 Drilling was completed 12/35 1935

Name of drilling contractor Humble Oil & Refg. Co., Address Houston, Texas

Elevation above sea level at top of casing 3619 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3825' to 3900' No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 2, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
13"OD	50#	8	SS	269	Tex-Pat.	None	None	None	
7-5/8"OD	29.70#	8	SS	1692	Hal.	"	"	"	
5-1/2" OD	14#	10	do	3812	Hal.	"	"	"	

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/2"	13"OD	290'	225	Halliburton	10.5#	105 tons used in well
9-7/8"	7-5/8"	1710'	500	"	10.5#	
8-3/4"	5-1/2"	3825'	125	"	10.5#	

PLUGS AND ADAPTERS

Heaving plug—Material ———— Length ———— Depth Set ————
Adapters—Material ———— Size ————

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		—————	—————			

Results of shooting or chemical treatment ————

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3900 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 12/23, 1935

The production of the first 24 hours was 55 barrels of fluid of which 99.6% was oil; %
emulsion; % water; and .2% sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in. ————

EMPLOYEES

L. J. Willis, Driller G. R. Cherry, Driller
E. Slayton, Driller V. A. Ayers, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 8

Midland, Texas, Jan. 8, 1936

day of Jan., 1936

Name R. B. Barker

Position Division Superintendent

Representing Humble Oil & Refining Co.
Company or Operator

My Commission expires

Address Drawer W, Midland, Texas

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	42	42	Caliche
42	123	81	Caliche & red beds
123	200	77	Hard sand
200	300	100	Hard sand and red beds
300	370	70	Red beds
370	380	10	Hard sand
380	946	66	Red beds
946	1020	74	Hard sand
1020	1080	60	Hard red beds
1080	1145	65	Red beds with streaks anhy.
1145	1282	137	Red beds
1282	1554	272	Hard red beds
1554	1609	55	Anhydrite
1609	1679	70	Salt
1679	1689	10	Salt and streaks of anhydrite
1689	1752	63	Anhydrite
1752	1882	130	Salt and potash streaks
1882	1920	38	Anhydrite
1920	1950	30	Salt and potash
1950	1962	12	Anhydrite
1962	1982	20	Potash & Salt
1982	2000	18	Anhydrite
2000	2010	10	Potash and streaks salt
2010	2100	90	Potash & anhydrite
2100	2152	52	Anhydrite
2152	2230	78	Salt and streaks of anhydrite
2230	2264	34	Anhydrite
2264	2270	6	Salt and streaks anhydrite
2270	2295	25	Anhydrite
2295	2410	115	Salt
2410	2533	123	Salt with streaks of anhydrite
2533	2675	142	Salt and shells
2675	2782	107	Salt with streaks anhydrite
2782	2985	203	Salt and anhydrite
2985	3010	25	Hard anhydrite
3010	3215	205	Anhydrite
3215	3712	497	Gray lime
3712	3717	5	Lime streaks and sand
3717	3900	183	Gray lime - Total Depth