

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	<b>X</b>
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

October 27, 1949

Midland, Texas

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the  
Humble Oil & Refining Company N.M. State "B" Well No. 9 in the

Company or Operator SE/4 of SE/4 of Sec. 29, T. 21-S, R. 36-E, N. M. P. M.,  
Bunice Monument Field, Lea County.

The dates of this work were as follows: 10-17-49 to 10-24-49

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on 9-2-49 19\_\_\_\_  
and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Set Baker Model K Retainer at 3868'. Perforated from 3830' to 3866'. Ran tubing and rods. Pumped well 12 hours and made 96.55 bbls. fluid, 13% water. On 24 hr. test made 7.55 bbls. oil plus 55% water. Gas vol. 24 MCF per day. GOR 3179. Tested 24 hrs. and made 3½ bbls. oil plus 80% water. GOR 3160. Loaded hole with oil. Spotted 20 gallons jel seal on bottom and 1000 gal. Dowel 15% LT acid. Flushed acid from casing with 24 bbls oil. Pumped 52.9 bbls oil with 2.4% water in 24 hrs. GOR 4330. Pumped 51.94 bbls oil in 24 hours. GOR 1059. Pumped well 24 hours and made 52 barrels PLO. Gas vol. 232 MCF per day. GOR 4428. Present completion depth 3868'.

Witnessed by \_\_\_\_\_ Name \_\_\_\_\_ Company \_\_\_\_\_ Title \_\_\_\_\_

Subscribed and sworn before me this \_\_\_\_\_  
27th day of October 1949

Jurle M. Bates

Notary Public

My commission expires 6-1-51

I hereby swear or affirm that the information given above is true and correct.

Name R. S. Dewey

Position Division Petroleum Engineer

Representing Humble Oil & Refining Company  
Company or Operator

Address Box 1600, Midland, Texas

Remarks:

Roy Garburegh  
Name \_\_\_\_\_  
Title \_\_\_\_\_

APPROVED