

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TR
(Other Instruct
Reverse Side)

CATE
ON

Project No. 100-100-100-100
FIDUCIARY AUGUST 31, 1985
LEASE DESIGNATION AND SERIAL NO.
NM-062648

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Conoco Inc.	8. FARM OR LEASE NAME Lockhart A 30
3. ADDRESS OF OPERATOR PO Box 410 Hobbs, NM 88240	9. WELL NO. 2
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FmH - 660 FmH - Unit header A	10. FIELD AND POOL, OR WILDCAT Eumant-Yates
14. PERMIT NO. 30-025-04833	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 30-215-36E
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH Dea
	13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

☐
☐
☐
☐
☐

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

☐
☐
☐
☐
☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

☐
☐
☐
☐

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

☐
☐
☐
☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

12/5/89 Notified BLM before RU. Miru. Installed BOP - 42.5 mon.
RTH w/101 fts 2-3/8" work string. Jagged a 3062' KB. Circ. 35 sx
salt gel in 75 bbl brine. Mix 25 sx class "c" cmt. (14.8H/gal) pumped
down. Perf 5-1/2" at 1850' KB w/ 4-1/2" JH. Perf at 1700' KB
with 4-1/2" JH. headed csg. Press to 1000 psig. Mix 25 sx.
cmt. Spot 10 sx Class "c" from 65' to surface. Flush/clean.
Mix 35 sx class "e" into 5-1/2" x 7-5/8" annulus at 150 psig.
Flushed lines. Removed Bop. Install dry hole marker.
Rebrace location.

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED W W Baker W W Baker

TITLE Administrative Sponsor

DATE 1/26/90

(This space for Federal or State office use)

APPROVED BY Orig. Signed by Adam Salameh

TITLE PRODUCTION MANAGER

DATE 2-26-90

CONDITIONS OF APPROVAL, IF ANY:

Approved as to conditions of approval.
Liability under bond is retained until
surface restoration is completed.

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.