

Form C-102  
**DUPLICATE**

**OIL CONSERVATION COMMISSION**

Santa Fe, New Mexico

**MISCELLANEOUS REPORTS ON WELLS**

OIL CONSERVATION COMMISSION  
 SANTA FE, NEW MEXICO.  
**RECEIVED**  
 OCT 21 1947

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<b>X</b>		

**HOBBS OFFICE**

**October 17, 1947**

Date

**Midland, Texas**

Place

OIL CONSERVATION COMMISSION,  
 SANTA FE, NEW MEXICO.  
 Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

**The Texas Company** **J. K. Rector Lease** Well No. **1** in the \_\_\_\_\_  
 Company or Operator Lease

**NE 1 SE 1** of Sec. **30**, T. **21-S**, R. **36-E**, N. M. P. M.,  
**Funice** Field, **Lea** County.

The dates of this work were as follows: **Comp. SP&A 12 Noon 10-6-47**

Notice of intention to do the work was (was-not) submitted on Form C-102 on **August 15** 19 **47**  
 and approval of the proposed plan was (was-not) obtained. (Cross out incorrect words.)

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

**13" casing cemented at 404 with 100 Sacks**

**9-5/8" casing cemented at 3243' with 500 sacks of cement**

**7" casing cemented at 3902' with 100 sacks cement.**

**This well was Salvaged, plugged and abandoned as follows:**

**(See reverse side)**

Witnessed by \_\_\_\_\_  
 Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

**17th** day of **October**, 19 **47**

Name **C. J. Holliman**

**Mary L. Cochran**  
 Notary Public

Position **Dist. Supt.**

Representing **The Texas Company**  
 Company or Operator

My commission expires **June 1, 1949**

Address **Box 1270, Midland, Texas**

Remarks:

**APPROVED**

**OCT 23 1947**

**Roy Garbrough**  
 Name  
**GAS INSPECTOR**  
 Title

Spotted cement plug of 20 sacks from 3335-3235 (in the 7" Casing)

Parted and pulled 7" casing at 2800'

Parted and pulled 9-5/8" casing at 700' and spotted cement plug of 30 sacks from 725'-675'. (in the top of the parted 9-5/8" casing)

Spotted cement plug of 30 sacks from 390-368' (In the bottom of the 13" casing. The required 4" pipe marker was cemented in the top of the hole with 20 sacks leaving all 13" casing cemented in the hole. Completed work 12 Noon 10-6-47. Hole was filled with heavy mud between plugs and all mud and cement plugs were spotted by pumping in through tubing. Location has been cleaned up and is now ready for inspection.