1CR

# N: MEXICO OIL CONSERVATION C MISSION

Santa Fe, New Mexico

#### **MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

NOTICE OF INTENTION TO TEST CASING SHUT-OF	F X	NOTICE OF I CHEMICAL	NTENTION TO SHO LLY TREAT WELL	OT OR
NOTICE OF INTENTION TO CHANGE PLANS	_	NOTICE OF I	NTENTION TO PUI SE ALTER CASING	LL OR
NOTICE OF INTENTION TO REPAIR WELL	-	<del></del>	NTENTION TO PLU	
TOTICE OF INTENTION TO DEEPEN WELL	_			
		<u> </u>		
		k, Texas,	February 6,	1937
IL CONSERVATION COMMISSION,	•			12.106
anta Fe, New Mexico.				
entlemen:			THE TEX	AS COMPANY
'ollowing is a notice of intention to do certain wo			ne	
	. Rect		_Well No	SE-1/4
Company of Operator Sec. 30 Company of Operator R 36	E .N	Lease . M. P. M.,	Eunice	Fie
Lea		,		
FULL DETAILS ( FOLLOW INSTRUCTIONS IN THE  T. D. 1550' Anhydrite.  Set and cemented 1526' o  51 Jts) at 1545' with 700 sa	f 9-5/8	ND REGULATIONS	s of the commiss	ss casing
T. D. 1550' Anhydrite. Set and cemented 1526' o 51 Jts) at 1545' with 700 sa ementing at 6AM 2-6-37. Anticipate drilling plug	f 9-5/8	nd regulations  3" <b>QD 40#</b> 8  Toro commo	of the commissions and seamles on cement.	ss casing Completed
T. D. 1550' Anhydrite. Set and cemented 1526' o 51 Jts) at 1545' with 700 sa sementing at 6AM 2-6-37. Anticipate drilling plug	f 9-5/8	nd regulations  3" <b>QD 40</b> # 8  Toro commo	of the commission seamle:	ss casing Completed sure method
T. D. 1550' Anhydrite. Set and cemented 1526' of 51 Jts) at 1545' with 700 sagementing at 6AM 2-6-37.  Anticipate drilling plug at 6AM 2-9-37.	f 9-5/8	osting casi	of the commission seamles on cement.	ss casing Completed sure method
T. D. 1550' Anhydrite. Set and cemented 1526' o 51 Jts) at 1545' with 700 sa sementing at 6AM 2-6-37.  Anticipate drilling plug at 6AM 2-9-37.	f 9-5/8	osting casi	of the commission seamles on cement.	ss casing Completed sure method
T. D. 1550' Anhydrite. Set and cemented 1526' o 51 Jts) at 1545' with 700 sa sementing at 6AM 2-6-37.  Anticipate drilling plug at 6AM 2-9-37.	f 9-5/8	osting casi	Sthd seamles on cement.  Ing by press  TEXAS CON	ss casing Completed sure method
T. D. 1550' Anhydrite. Set and cemented 1526' o 51 Jts) at 1545' with 700 sa sementing at 6AM 2-6-37.  Anticipate drilling plug at 6AM 2-9-37.	f 9-5/8 cks El and te	osting casi	Sthd seamles on cement.  Ing by press  TEXAS CON	ss casing Completed sure method
T. D. 1550' Anhydrite. Set and cemented 1526' o 51 Jts) at 1545' with 700 sa sementing at 6AM 2-6-37.  Anticipate drilling plug at 6AM 2-9-37.	f 9-5/8 cks El and te	Toro common sting casi  Send common serior common string casi  TE	Sthd seamles on cement.  Ing by press  TEXAS CON	ss casing Completed sure method sure method with the sure method with th
T. D. 1550' Anhydrite. Set and cemented 1526' o [51 Jts) at 1545' with 700 sa sementing at 6AM 2-6-37.  Anticipate drilling plug at 6AM 2-9-37.	f 9-5/8 cks El and te	Toro common string casi  Send common string casi  Transfer casi  Send common case case common case case common case case case case case case case case	Sthd seamles on cement.  Ing by press  Company or Operations ragar	ss casing Completed sure method sure sure method sure

## Confidence and Confidence of the Confidence of t

### Engine a necesion de la compa

## The Committee of the Co

The state of the s

•

.