

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLE
COPIES

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Conoco Inc.	8. FARM OR LEASE NAME Lockhart B-31
3. ADDRESS OF OPERATOR P.O. Box 460 - Hobbs, New Mexico 88240	9. WELL NO. 7
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2080' FNL & 330' FWL - Unit Letter E	10. FIELD AND POOL, OR WILDCAT Jalmat Water 7 Res Tr
14. PERMIT NO. 30-025-04855	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 31-21 S - 36 E
15. ELEVATIONS (Show whether DT, RT, GR, etc.)	12. COUNTY OR PARISH Lea
	13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	PULL OR ALTER CASING
FRACTURE TREAT	MULTIPLE COMPLETE
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANS
(Other)	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) MIRR. Kill well w/ 10 #/gal mud if necessary. Run csq scraper to 3800' & POOH.
- 2) Set CIBP at 3780'. Load hole w/ 10 #/gal mud & test CIBP to 1000 psi for 15 mins. Pump 50 sacks class "C" cement to plug well back from 3780' - 3300'. Displace cement w/ 13 bbls 10 #/gal mud. Pull up to 1950'. Pump 50 sacks class "C" cement to plug from 1950' - 1470'. Displace cement w/ 6 bbls 10 #/gal mud. Pull up to 250'. Pump 25 sacks class "C" cement to plug well back from 250' to surface. POOH & fill csq to surface w/ cement.
- 3) Cut off csq 3' below ground level. Install P&A marker. For further information contact Jay Vashler at 397-5866

18. I hereby certify that the foregoing is true and correct

SIGNED DAVID F. FINNEY

TITLE Administrative Supervisor

DATE March 6, 1989

(This space for Federal or State office use)

APPROVED BY CHIEF OF BUREAU
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE 3-9-89

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

BLM - (advised) (6) rec'd (2) approved (1) file