

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	X
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER) Fract treat	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
 SANTA FE, NEW MEXICO

Hobbs, New Mexico
 (Place)

June 19, 1959
 (Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation **Arnett Ramsey (NCT-D)** Well No. **6** in **K**
 (Company or Operator) **Lease** (Unit)
NE $\frac{1}{4}$ **SW** $\frac{1}{4}$ of Sec. **33**, T. **21-S**, R. **36-E**, NMPM., **Emont** Pool
 (40-acre Subdivision)
Lee County.

FULL DETAILS OF PROPOSED PLAN OF WORK
 (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 3880'. FBD 3876'. Producing interval 3800-3835'. It is proposed to perforate, fract treat and drill deeper as follows:

- 1. Perforate 5 $\frac{1}{2}$ " csg 3778-80', 3758-60', 3856-58' with 2. 1/2" JHPT.**
- 2. Straddle perfs 3856-58' and treat with 4000 gals lse oil with 1/20# Adomite & 1-3# SPG. Straddle perfs 3800-35'. Treat with 3000 gals lse oil with 1/20# Adomite & 1-3# SPG. Straddle perfs from 3758-80' and treat with 8000 gals, 1/20# Adomite and 1-3# SPG. Straddle all perforations. Swab and test.**
- 3. Drill deeper to 3908'. If swab test is satisfactory, fracture treat below Lynes packer set in the interval 3878-84' with 10,000 gals lse oil in 2 stages, 1/20# Adomite and 1-3# SPG.**

Approved....., 19.....
 Except as follows:

Approved
 OIL CONSERVATION COMMISSION
 By *John W. Ramsey*
 Title.....

Gulf Oil Corporation
 (Company or Operator)
 By *C. M. Bumpass*
 Position **Area Petroleum Engineer**
 Send Communications regarding well to:
 Name **Gulf Oil Corporation**
 Address **Box 2167, Hobbs, N. M.**