

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

If State Land submit 6 Copies

ARI LOCATE	EA 640 ACRES WELL CORRE	CTLI				William A	. Ramsay "A"
			tion			(Lease)	
No	36	in SE	¼ ofSW	, of Sec34	Т	21-S, R	36-E., NMPM.
	IImdoni	anat od		Pool.	7: <u>1</u>	.a	
	//0		South	line and	.980	feet from	esoune
	07 76	** 0.	or and the Oil and	Ges Lesse No. is	D-	-1132	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
		12-9	1	9.57 Drilling	was Completed	LL_L	±, 19c.J
ing Comm	- a Contracto	- Aut	ur Budge Dr	illing Co		***************************************	
		Box	695, Odessa	, ICAAD			***************************************
lress		T of Tubing	Heed 3	5651	The info	rmation given is to b	e kept confidential until
ation above	e sea level at		, 19				
•••••••••••				SANDS OR ZO	NES		
	20501	4-	38161	No. 4,	from	to	***************************************
1, from	3750	to.		No. 5.	from	to	
2, from			***************************************	No 6	from	to	
3, from		to.		110. 0,			
				TANT WATER			
lude data (on rate of wa	ter inflow and	elevation to which	water rose in hole	: .		
1, from		•••••	to			.feet	
			to			.feet	
			to			.feet	
4. from			to			feet.	
1				CASING RECO			
	WEIGH	T NEW)R	KIND OF	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
SIZE	PER FO						Surface Pipe
5/8"	24# 14#	Ne Ne	2 2 2 2 2	Baker Baker		3750-38361	Production Stri
_1/2" _	14#	No					
				<u> </u>			
			MUDDING	AND CEMENT	ING RECORD		
SIZE OF	SIZE OF	WHERE SET	NO. BACKS OF CEMENT	METHOD USED		MUD GRAVITY	AMOUNT OF MUD USED
HOLE	CASING			Pump & Pli	10		
2-1/4" 7-7/8"	8-5/8"	<u> 397!</u> _3859!	325 800	Pump & Pli	-		
1-1/0	J= <u>1</u> /2						
			1		AND SERVICE A	TION	
				PRODUCTION			
		(Record	the Process used, I	No. of Qts. or G	als. used, interval	treated or shot.)	
Spotte	ed 250ga	llons mud	acid on per	forations f	rom 3750-38	16! and squeen	zed into formatio
mant	ed format	ion with	20,000 gallo	ns refined	oil with 1#	SPG in 4 stag	ges of 5,000 gall
Trear	er Tarmer	05 hall o	ealers in 10	bbls oil b	etween each	stage.	
each.	Pumped	2) Uall 3	Caror D att ==				
	•	·····			OI 1	on thm: 2 2/0	tubing 21, hours
esult of P	roduction Stir	nulationF]	owed 192 bbl	s oil and l	U4 DDIS Wai	<u> </u>	" tubing 24 hours
				***************************************	**********************		
	*					Depth Cleaned	Out
**********							\\\\

TEOORD OF DRILLSTEM AND SPECIAL TET'S

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Cable to	ools were	used from	fee	et to	feet,	and fron	n	feet to
					DUCTION	,	***************************************	leet to
Put to 1	Producing	······	January 1,					
			ction during the first 24	hours was	. 296		barrels of li	iquid of which65
	W	as oil;	% wa	s emulsion;	.35	% wa	ter; and	
	G	ravity	34.0		••			
GAS WI	ELL: T	he produc	tion during the first 24	hours was		MCF		barrels
	lie	quid Hydr	ocarbon. Shut in Pressur	re 11	•	M.C.F.	pius	barrels
Length .								
1 11	ASE IN	DICATE	Southeastern New	N TOPS (IN CO	NFORMAN	NCE WI	TH GEOGI	RAPHICAL SECTION OF STATE)
Γ. Anh	y							Northwestern New Mexico
				- Locy Ollian				Ojo Alamo
R Cole								Kirtland-Fruitland
T. Yates3072! T. Sim								Farmington
7 Ri	vers. 332 368	<u>دا</u> 51	Т					Pictured Cliffs
			T	Ellenburger	· ·	••-••	т.	Point Lookout
			T					Mancos
			T.	. Orannec				Dakota
				• •				Morrison
			Т.					Penn.
			т.					
			Т.	***************************************	• • • • • • • • • • • • • • • • • • • •	••••		
141122	**************		т.	***************************************				
1		Till	1	FORMATIC	ON RECO	RD		
From	То	Thickness in Feet	Formati	ion	From	То	Thickness in Feet	Formation
0	9		Distance from	Top Kellv				
	1.5		Drive bushing	to Ground				DEVIATION - TOTOO SU
	45 401		Surface Sand a	nd Caliche				3/4 - 3501
	530		Red Bed and She	ells				1/2 - 9001
	1230 1780		Red Bed	• .				3/4 - 1700 · 2 - 2400
	2925		Shale andAnhydı Salt and Anhydı	rite rite				1-1/2 - 2700
	3405		Anhydrite	- 06				1 - 2975
	3860		Lime					3/4 - 3240 3/4 - 3625
		ļ						3/4 - 3025
	!							
		i						
				·				
				į				
			ATTACH SEPARAT	े ता कवायात स	DDITTO	<u>-</u>		
I hereb	V Swene -	γr. α# ·	ATTACH SEPARAT					
an be de	, awcar (termined	n amrm t from avai	that the information given ilable records.	en herewith is a c	complete and	d correct	record of th	ne well and all work done on it so far
		aval	MADIE ICCOTUS.					
เกลทบ ^-	Opense	. G1174	' 011 Camer					ruar) 13, 1958
יים עווייים	Operator		· Cil Corporatio	n	Address	.Box 2	167. Ho	bos, New mexico
· /	ニーノ		~. 1/4 /	-				of Prod.