

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
B-1732	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL ☐ GAS ☒ WELL ☐ OTHER ☐		7. Unit Agreement Name
2. Name of Operator Gulf Oil Corporation		8. Farm or Lease Name Harry Leonard (NCT-C)
3. Address of Operator P. O. Box 670, Hobbs, NM 88240		9. Well No. 8
4. Location of Well UNIT LETTER <u>H</u> 1980 FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>21S</u> RANGE <u>36E</u> N.M.P.M.		10. Field and Pool, or Wildcat Eumont Gas
15. Elevation (Show whether DF, RT, GR, etc.) 3480' GL		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	
		OTHER <u>Squeezed Existing Perfs, Reperfed,</u> ☒ <u>Acidized & Fracd</u>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

POH with tubing and packer. Set cement retainer at 3518.5'. Pumped 150 sacks Class "C" cement with .3% Halad 4 .04% CFR2. WOC. Spot 250 gals 15% NEFE double inhib HCL 3500'-3250'. Perf 3359-61', 3384-86', 3411-13', 3469-71', 3486-88' with (2) 1/2" decent burrless o-phase JHPF (20 holes). Acidize with 3500 gals 15% NEFE slick HCL & (30) 7/8" RCNB's. Max pres 3700#, AIR 5.5 BPM, ISI 1500#, 15 min 1300#. Pumped 250 gals 15% NEFE; frac with 60,000# 20/40 sand, 1000 gals foamed 15% NEFE acid and (16) 7/8" RCNB's. Max pres 4500#, min 4100#, avg 4300#, AIR 15.0 BPM, ISIP 3200#, 5 min 2700#, 10 min 2600#, 15 min 2600#, 3 hrs 1150#. Complete after P&A Arrowhead, perfg, acidizing & fracing Eumont 12-29-80.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. D. Pitzer TITLE Area Engineer DATE 1-5-81

APPROVED BY [Signature] TITLE [Signature] DATE [Signature]
CONDITIONS OF APPROVAL, IF ANY: