

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

1955 OCT 21 AM 9:53

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION TO CLEANOUT (OTHER) & TREAT W/CHEMICALS	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

October 22, 1956
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the State (Sec. 2)

Shell Oil Company Well No. 10 in T
(Company or Operator) (Unit)
NW 1/4 SW 1/4 of Sec. 2, T. -21-S, R. -37-E, NMPM., Hare Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

We propose to do the following:

1. Pull tubing.
2. Run tubing w/bit & clean to bottom.
3. Run tubing w/packer & retrievable bridging plug.
4. Set plug on bottom & packer between 7789' & 7920'.
5. Load one 2000-gallon paddle mixer w/70 gallons Control-Flow & fill w/lease oil. Load one 3000-gallons paddle mixer w/105 gallons Control-Flow & fill w/lease oil.
6. Treat below packer w/1200 gallons of mixture. Overflush w/10 bbls. lease oil.
7. Reset plug between 7789' & 7920' & packer 7699' & 7727'.
8. Treat below packer w/1700 gallons of mixture. Overflush.
9. Reset plug between 7699' & 7727' & set packer above 7600'.
10. Treat below packer w/remaining mixture (approx. 2100 gallons). Overflush w/10 bbls. lease oil.
11. Pull tubing, packer & bridging plug.
12. Run tubing w/HL packer.
13. Set packer above all perforations.
14. Swab well in & place on production.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Shell Oil Company
Company or Operator

By..... B. Nevill
Original signed by..... B. Nevill

Position..... Division Exploitation Engineer
Send Communications regarding well to:

Name..... Shell Oil Company
Address..... Box 1957, Hobbs, New Mexico