

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

RECEIVED  
OCT 24 1950

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	<input type="checkbox"/>
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	<input type="checkbox"/>	REPORT ON PULLING OR OTHERWISE ALTERING CASING	<input type="checkbox"/>
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input type="checkbox"/>	REPORT ON DEEPENING WELL	<input type="checkbox"/>
REPORT ON RESULT OF PLUGGING OF WELL	<input type="checkbox"/>		<input type="checkbox"/>

October 24, 1950 - Hobbs, New Mexico  
Date Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO,  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the  
**Stanolind Oil & Gas Company J. P. Alexander "B"** Well No. **1** in the  
Company or Operator Lease  
**NW/4** of Sec. **5** T. **21-S** R. **37-E**, N. M. P. M.,  
**Hardy** Field **Lea** County.

The dates of this work were as follows: **9-15-50 to 9-22-50, Inc.**  
Notice of intention to do the work was (~~was~~) submitted on Form C-102 on **May 10** 19**50**  
and approval of the proposed plan was (~~was~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The uncemented portion of casings were pulled and cement plugs placed as follow:

Casing Salvaged Size	Amount	Cement Plug Intervals	Mud Laden Fluid Intervals
7"	2370' 10"	30 sx. 3516-3366'	3366-1550'
9-5/8"	59'	20 sx. 1550-1450'	1440-26'
		20 sx. 26-Surface	

Witnessed by **T. S. Holden** **Stanolind Oil & Gas Company** **Head Rsht.**  
Name Company Title

Subscribed and sworn before me this **25th**

day of **October** 19**50**

*Ella Collins*  
Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name **Kolambright J.**

Position **Field Engineer**

Representing **Stanolind Oil and Gas Company**  
Company or Operator

My commission expires **5-31-53**

Address **Box "F"; Hobbs, New Mexico**

Remarks:

*Way Yarbrough*  
Oil & Gas Inspector  
Name

Title

After plugging, a 4" marker extending 4' above the ground level was erected and location leveled to conform with surrounding terrain.