

## MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New MexicoJan. 22, 1938

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.  
Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as \_\_\_\_\_

Stanolind Oil & Gas Co. Hill "C" Well No. 3 in NW 1/4  
Company or Operator of Sec. 5, T. 21S, R. 37E, N. M. P.M., Barby Lease Lea County.  
N. The well is 660 feet (N.) (S.) of the 1st North line and 660 feet

Hill									
C-3									

(E.) 660 of the West line of NW Corner Section 5

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. \_\_\_\_\_, Assignment No. \_\_\_\_\_

If patented land the owner is Elmer C. Hill

Address Emice, New Mexico

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is Stanolind Oil & Gas Company

Address Philcade Building, Tulsa, Oklahoma

AREA 640 ACRES  
LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows: Rotary tools to approximately 3550, set casing and complete with cable tools.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: Bond on file with commission

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
17"	15" OD	40#	New	300	Cemented	To Surface
12 1/2"	9-5/8" OD	36#	"	1400	"	500
8-3/4"	7" OD	22#	"	3500	"	275

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 3700 feet.

Additional information: We propose to drill with the above methods and casing program to a depth of about 3800', unless oil or gas in commercial quantities is encountered at a lesser depth. All work to conform to approved practice and in conformance with regulations of the Oil Conservation Commission of New Mexico

Approved \_\_\_\_\_, 19\_\_\_\_  
except as follows:

Sincerely yours,

Stanolind Oil & Gas Co.

Company or Operator

By Laesa L. Hendrickson

Position Field Superintendent

Send communication regarding well to

Name R. L. Hendrickson

Address Box F, Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By Ernest Sheppard  
Oil & Gas Inspector  
Title \_\_\_\_\_

JAN 25 1938