NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

CORRECTED REPOR

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A conveil be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rojection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is considered. See additional instructions in the Rules and Regulations of the Commission.

ional instructions in the Rules and Re	Indicate Nature of Notice by Ch	ecking Below	$\sqrt{}$
OTICE OF INTENTION O CHANGE PLANS	Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper	
OTICE OF INTENTION O PLUG WELL	Notice of Intention to Plug Back	Notice of Intention to Set Liner	
VOTICE OF INTENTION O SQUEEZE	Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)	
Jotice of Intention o Gun Perforate	Notice of Intention (Other) rest casing	Notice of Intention shut offOther)	
OIL CONSERVATION COMMISSIC SANTA FE, NEW MEXICO	ON San Angelo, Te	exas May 30,	1953
Gentlemen:	land the design of	she M.D. Cuppy	
		the	
(Company or O	perator)		(Unit)
1/4 SE 1/4 of Sec	7, T, R3.7	,NMPM., Har dy	Po
= _ =			
(FOI	County. FULL DETAILS OF PROPOSED LLOW INSTRUCTIONS IN THE RUI		
Spudded 5-25-53. Reilled to TD 1296'	FULL DETAILS OF PROPOSED LLOW INSTRUCTIONS IN THE RUI	ed 8-5/8" casing at TD	12961
Spudded 5-25-53. Bailled to TD 1296; with 310 sacks cemen	FULL DETAILS OF PROPOSED LLOW INSTRUCTIONS IN THE RUI 5-28-53, ran & comentont, Halliburton method	LES AND REGULATIONS)	•
Spudded 5-25-53. Bailled to TD 1296; with 310 sacks cemen	FULL DETAILS OF PROPOSED LLOW INSTRUCTIONS IN THE RUI 5-28-53, ran & comentont, Halliburton method	ed 8-5/8" casing at TD with cement to surface	•
Spudded 5-25-53. Bailled to TD 1296; with 310 sacks cemen	FULL DETAILS OF PROPOSED LLOW INSTRUCTIONS IN THE RUI 5-28-53, ran & comentont, Halliburton method	ed 8-5/8" casing at TD with cement to surface	•
Spudded 5-25-53. Bailled to TD 1296; with 310 sacks cemen	FULL DETAILS OF PROPOSED LLOW INSTRUCTIONS IN THE RUI 5-28-53, ran & comentont, Halliburton method	ed 8-5/8" casing at TD with cement to surface	•
Spudded 5-25-53. Bailled to TD 1296; with 310 sacks cemen	FULL DETAILS OF PROPOSED LLOW INSTRUCTIONS IN THE RUI 5-28-53, ran & comentont, Halliburton method	ed 8-5/8" casing at TD with cement to surface	•
Spudded 5-25-53. Brilled to TD 1296; with 310 sacks ceme; will let stand 48 h.	FULL DETAILS OF PROPOSED LLOW INSTRUCTIONS IN THE RUI 5-28-53, ran & comentont, Halliburton method	ed 8-5/8" casing at TD with cement to surface	•
Spudded 5-25-53. Bailled to TD 1296; with 310 sacks cemen	FULL DETAILS OF PROPOSED LLOW INSTRUCTIONS IN THE RUI 5-28-53, ran & cement on the state of the	ed 8-5/8" casing at TD with cement to surface	•
Spudded 5-25-53. Brilled to TD 1296* with 310 sacks cemes Will let stand 48 h	FULL DETAILS OF PROPOSED LLOW INSTRUCTIONS IN THE RUI 5-28-53, ran & comentont, Halliburton method	ed 8-5/8" casing at TD with cement to surface test for easing shut of the company of Operator Partner	off.
Spudded 5-25-53. Brilled to TD 1296* with 310 sacks cemes Will let stand 48 h	FULL DETAILS OF PROPOSED LLOW INSTRUCTIONS IN THE RUI 5-28-53, ran & cementer of the course that the desired ours than drill plug & By	ed 8-5/8" casing at TD with cement to surface test for easing shut o	off.
Spudded 5-25-53. Brilled to TD 1296; with 510 sacks cemes Will let stand 48 h. Approved	FULL DETAILS OF PROPOSED LLOW INSTRUCTIONS IN THE RUI 5-28-53, ran & cementer of the course that the desired ours than drill plug & By	ed 8-5/8" casing at TD with cement to surface test for easing shut of the company of Operator Send Communications regarding we	ell to: