

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office San Antonio
Lease No. 03174 (3)
Unit N.M.P.U.

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

W. C. Hook 3-6 No. 3

Hobbs, New Mexico August 23, 1962

Well No. 3 is located 660 ft. from N line and 1980 ft. from E line of sec. 8

SE 1/4 Section 8
(1/4 Sec. and Sec. No.)

213
(Twp.)

37E
(Range)

N.M.P.U.
(Meridian)

Drinker
(Field)

Lee
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with rotary tools at the above location to a depth of approximately 6600' unless commercial oil or gas production is encountered at a lesser depth. All casing points will be cemented in accordance with approved methods of the U. S. Geological Survey and any other special requirements will be complied with.

The following casing pattern will be used: 13 3/8" casing will be set at approximately 250' and cemented with 240 sacks cement. 9 5/8" casing will be set at approximately 2825' and cemented with sufficient cement to protect the salt section estimated at 1800 sacks. 7" casing will be set at total depth and cemented with approximately 90 sacks cement, amount to be determined from Caliper survey. 5" casing will be perforated opposite main pay zone.

Approval to produce this well upon completion is also requested.
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box 427

Hobbs, New Mexico

By

Title District Superintendent