

UNITED STATES ^{AM '65} DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 031741 B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

NMFU

8. FARM OR LEASE NAME

Hawk B-1

9. WELL NO.

7

10. FIELD AND BOOY, OR WILDCAT

NMFU Field
Blinebry

11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA

9-21S-37E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Continental Oil Company

3. ADDRESS OF OPERATOR
Box 460, Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
660' FSL & 660' FEL of Section 9, Township 21S,
Range 37E, Lea County, New Mexico, NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3472 DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Squeeze & Reperf

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Subject well squeezed and reperforated using the following procedures: Before Workover - TD 6750, PB 6475 DF 9' Pay-Blinebry 5782-5982. Perfs 5782, 5787, 5800, 5804, 5811, 5814, 5937, 5953, 5960, 5970, 5976, & 5982 W/1 JSPF. Work Done - Squeezed perfs 5782-5982 W/130 sx Class "C" Cement. Perforated 5738, 5761, 5768, 5783, 5792, 5804, 5813, 5821, 5828, 5843 W/1 JSPF. Acidized W/1000 gals 15% HCL W.5% HC-2 using 15 Ball Sealers. Fraced W/22,000 gals crude 20,000# sd, 950# "ADOMITE" & 55 gals FR3. After Workover No change in TD or PB, Pay - Blinebry - 5738-5843. Perf 5738, 5761, 5768, 5783, 5792, 5804, 5813, 5821, 5828, 5843. IP pmpd 13 bbls 39° gravity oil, no water, in 24 hours, 247 MCFGPD, GOR 19,000. Daily allow 14 BO. Work started 5-29-65, Completed 6-14-65. Tested 8-12-65.

APPROVED

AUG 24 1965

J. L. GORDON
ACTING DISTRICT ENGINEER

18. I hereby certify that the foregoing is true and correct

SIGNED SIGNED: HAL R. STEPHENS

TITLE Staff Supervisor

DATE 8-20-65

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

USGS-5, NMOCC, 2 FILE, PAN AM HOBBS,-3, ATL ROS-2, STD HOUS. & MID-1 each

*See Instructions on Reverse Side