

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Las CrucesLease No. 031781 1-1Unit H. F. U.

FEB 21 1951

RECEIVED
U. S. CONSERVATION COMMISSION
HOBBS OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	☒	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

W. C. Hard B-10 No. 1-X

Hobbs, New Mexico February 16, 1951

Well No. 1-X is located 990 ft. from N line and 1620 ft. from E line of sec. 10
NE/4 Sec. 10 23S 37E N.M.P.M.
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Brannon Lee New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with rotary tools at the above location to a total depth of approximately 7730'. All casing points will be cemented in accordance with approved methods of the U. S. Geological Survey and any other requirements will be complied with.

It is planned to use the following casing patterns: 10 3/4" casing to be set at approximately 250' and cemented with 250 sacks. Cement to be circulated to surface. 7 5/8" casing to be set at approximately 3100' and cemented with approximately 1000 sacks or sufficient cement to protect the salt section as determined by caliper survey. 5 1/2" casing to be set at approximately 7730' and cemented with approximately 600 sacks as determined by caliper survey. 5 1/2" casing to be perforated opposite pay section.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil CompanyAddress Bec: CCHobbs, New MexicoBy E. L. ShafferTitle District Superintendent