

STATE OF NEW MEXICO
OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

UNBILANECUS NOTICES

SUBMIT THIS NOTICE IN TRIPPLICATE TO THE DISTRICT OFFICE, OIL CONSERVATION COMMISSION, BEFORE THE WORK SPECIFIED IS TO BEGIN. A COPY WILL BE RETURNED TO THE SENDER ON WHICH WILL BE GIVEN THE APPROVAL, WITH ANY MODIFICATIONS CONSIDERED ADVISABLE, OR THE REJECTION BY THE COMMISSION OR AGENT, OF THE PLAN SUBMITTED. THE PLAN AS APPROVED SHOULD BE FOLLOWED, AND WORK SHOULD NOT BEGIN UNTIL APPROVAL IS OBTAINED. SEE ADDITIONAL INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION.

INDICATE NATURE OF NOTICE BY CHECKING BELOW:

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO ZONE BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO COURSE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (NITRO)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION TO (OTHER) (Specify) Complete		NOTICE OF INTENTION TO (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

November 3, 1953

(PLACE)

(DATE)

GENTLEMEN:

FOLLOWING IS A NOTICE OF INTENTION TO DO CERTAIN WORK AS DESCRIBED BELOW AT THE

Humble Oil & Refining Company, New Mexico State V, Well No. 1, in the
(COMPANY OR OPERATOR)
SW 1/4, SW 1/4, Sec. 20, T. 22 N., R. 37 E., N.M.P.M., Blinchesy-Drinkard, Pool
(LEASE SUBDIVISION)
Lea COUNTY, Case No. 1521
Order No. H-1207

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

- It is proposed to complete the above described well for dual oil production by replacing the single string of 2" LBS tubing with two strings of 1-1/2" non-upset tubing as follows:
1. Close upper circulating sleeve at 6484' and remove blanking plug at 6554'.
2. Test tubing with 1200 psi for 30 minutes.
3. Unlatch from tubing receptacle at 6549' and pull 2" LBS tubing.
4. Run long string of 1-1/2" non-upset tubing with dual string anchor placed at approximately 6680' and latch into tubing receptacle.
5. Test tubing with 1200 psi for 30 minutes.
6. Run short string of 1-1/2" non-upset tubing and latch into dual string anchor.
7. Open circulating sleeve at 6586'.
8. Swab in Drinkard.
9. Swab in Blinchesy.
10. Conduct packer leakage test.

In the application for dual completion, Humble indicated that the 2" tubing below the production packer would be replaced with 1-1/2". This was to be done to replace the 2" Garrett Oil Tools circulating sleeve with a 1-1/2" size. Garrett has recently developed a shifting tool that will

APPROVED
EXCEPT AS FOLLOWS:

Humble Oil & Refining Company
COMPANY OR OPERATOR

BY R. R. ALWORTH

POSITION Agent

SEND COMMUNICATIONS REGARDING WELL TO:

APPROVED
OIL CONSERVATION COMMISSION

NAMES Humble Oil & Refining Company

ADDRESS Box 2347, Hobbs, New Mexico

DATE