

NEW MEXICO OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

SUBMIT THIS NOTICE IN TRIPPLICATE TO THE DISTRICT OFFICE, OIL CONSERVATION COMMISSION, BEFORE THE WORK SPECIFIED IS TO BEGIN. A COPY WILL BE RETURNED TO THE SENDER ON WHICH WILL BE GIVEN THE APPROVAL, WITH ANY MODIFICATIONS CONSIDERED ADVISABLE, OR THE REJECTION BY THE COMMISSION OR AGENT, OF THE PLAN SUBMITTED. THE PLAN AS APPROVED SHOULD BE FOLLOWED, AND WORK SHOULD NOT BEGIN UNTIL APPROVAL IS OBTAINED. SEE ADDITIONAL INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION.

INDICATE NATURE OF NOTICE BY CHECKING BELOW

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (NITRO)	
NOTICE OF INTENTION TO RE-REFRACT	☒	NOTICE OF INTENTION (OTHER) Fracture	☒	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(PLACE)May 6, 1957
(DATE)

CERTIFICATE

FOLLOWING IS A NOTICE OF INTENTION TO DO CERTAIN WORK AS DESCRIBED BELOW AT THE

Humble Oil & Refining Company N. M. State V WELL NO. 1 IN M
(OWNERS OR OPERATOR) (UNIT)
SW 1/4 M. SW 1/4 OF SEC. 20, T. 21-S, R. 37-E, NMPL, Drinkard POOL
(LEASES SUBSIDIARY) Lea COUNTY

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Rig up unit and kill well.
2. Set Baker packer at 5550 feet. Set Baker Model C-1 receptacle assembly in packer with G. O. T. sleeve below packer in closed position.
3. Perforate casing opposite Blinbry from 5710-5760 feet and 5780-5850 feet.
4. Acid wash perforations with 500 gallons and fracture perforated interval with 20,000 gallons refined oil and 30,000 pounds of sand.
5. Swab and test.
6. Run 2-inch tubing string with G. O. T. sleeve valve above Baker receptacle sub in open position.
7. Swab in Blinbry gas. Close upper valve, open lower valve and swab in Drinkard.

Producing Interval: Perforated casing from 6625-6635 feet and 6642-6658 feet.
Current test: 10 B/D, no water, 10,621 GOR.

APPROVED _____ 19____
BY COMMISSIONERAPPROVED _____
BY OIL CONSERVATION COMMISSION

Humble Oil & Refining Company

BY J. B. Van Sankt
COMPANY OR OPERATORPOSITION Agent
SEND COMMUNICATIONS REGARDING WELL TO:

NAME Humble Oil & Refining Company

ADDRESS Box 2347, Hobbs, New Mexico