

**NEW MEXICO OIL CONSERVATION COMMISSION**  
Santa Fe, New Mexico

**MISCELLANEOUS NOTICES**

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL <del>Drill</del> <b>Cement Plugs</b>	<b>x</b>
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	<b>x</b>
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER) <b>Recomplete as gas well</b>	<b>x</b>

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

**Hobbs, New Mexico**  
(Place)

**February 16, 1954**  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the **New Mexico State V**

**Humble Oil & Refining Company**  
(Company or Operator) Well No. **2** in **N**  
(Unit)  
**SE**  $\frac{1}{4}$  **SW**  $\frac{1}{4}$  of Sec. **10**, T. **21S**, R. **37E**, NMPM., **Drinkard** Pool  
(40-acre Subdivision)  
**Lea** County.

**FULL DETAILS OF PROPOSED PLAN OF WORK**  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

The well was plugged and abandoned in May 1949.

**Objective:** The purpose of this workover is to drill out cement plugs, set a liner, and recomplete as a Tubb gas well.

**Intended Procedure:** It is intended to recomplete the well according to the following procedure: (1) move in and rig up light power rotary rig, (2) drill out cement to top of 5-1/2-inch casing with a 6-3/4-inch bit, (3) pull bit and run 4-3/4-inch bit with casing scraper and drill out bridging plugs and cement to 6370 feet, (4) set a cast iron bridging plug on bottom at 6370 feet with 10 foot cement on top, (5) run a 4-inch OD T&C liner to 5400' and cement to surface, (6) drill plug and spot oil or fresh water from 5600 feet to bottom and pull out of hole, (7) perforate casing from 6290 to 6340 feet, (8) run tubing and scrub and test, (9) treat with 500 gallons of mud acid and 3000 gallons of low tension acid, (10) scrub acid load and place on production.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By *S. G. Stanley*

Title *mcb/mcb*

**Humble Oil & Refining Company**  
Company or Operator

By *M. M. Rogers*

Position **District Superintendent**  
Send Communications regarding well to:

Name **Humble Oil & Refining Co.**

Address **Box 2347, Hobbs, N. M.**

