

COUNTY		Lea		FIELD		Brunson		STATE		N.M.		NO.		OWWO	
OPR.		Humble Oil & Refg. Co.										MAP			
NO.		3 LSE New Mexico-State "V"													
SEC.		10		T		21S		BLK.		37E		SUR		CO-ORD.	
LOC. 660' fr S Line & 1980' fr E Line of Sec.															
Re-		MI.		FROM		Re-		CLASS.		OWWO/P EL 3463 A					
SPUD.		5-5-63		COMP		6-30-63		FORMATION		DATUM		FORMATION		DATUM	
IRT.		250 Ac., SOF 10,000													
		+ 10,000# sd.													
CSG. & SX.															
		5 1/2" 7673' 485													
TBG.		DEPTH		SIZE											
LOGS		EL		GR		RA		IND		HC		A			
		OTD 7673'													
		PB													
PROD INT.		(DAILY RATE)		BS&W		GH		GOR		GTY		C. P.		T. P.	
		HRS. TEST													
NEW ZONE ABANDONED															
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.															
CONT.		PROP DEPTH										TYPE			
DATE															

F.R.C. 9-12-63, OWWO.
 9-9-63 OTD 7673', Completion Reported.
 Squeezed Perfs 7620-7655' with 50 sx.
 Re-Squeezed with 50 sx.
 Perf 1 shot @ 7461', 7493', 7507', 7512', 7515',
 7552', 7565', 7569', 7573', treated 250 gals acid,
 SOF 10,000 gals + 10,000# sd.
 Did not recover the load.

COUNTY	Lea	FIELD	Blinebry & Drinkard	STATE	N.M.	NO.	OWWO
OPR	Humble Oil & Refg. Company						MAP
NO.	3	LSE	New Mexico-State "V"				
SEC.	10	T.	21S	BLK.	37E	SUR.	CO-ORD.
LOC.	660' fr S Line & 1980' fr E Line of Sec.						
Re-	MI.	FROM	(Bli. & Drkd)	CLASS.	own/EL 34632		
SPUD.	11-24-63	COMP.	12-23-63	FORMATION	DATUM	FORMATION	DATUM
TRT.							
CSG. & SX.							
	10 3/4"	326'	300				
	7 5/8"	3082'	1600				
	5 1/2"	7673'	485				
TBG.	DEPTH	SIZE					
LOGS	EL	GR	RA	IND	HC	A	
				TD	7673'	PB	7405'
PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.	T. P.
5710-5800'	Flwd 181 BO + 4 BW 3/16"						700# 24
(Blinebry)							
6477-6500'	Flwd 59 BO + 2 BW 24/64"						300# 24
(Drinkard)							
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.							
CONT.				PROP DEPTH	TYPE		
DATE							

1-13-64 F.R.C. 1-16-64; OWWO, OTD 7673'. Elev. 3463' Df
 TD 7673', PB 7405', COMPLETED.
 Set CIEP @ 7405'.
 Squeezed perms 7461-7573' W/400 sx.
 Perf (Drinkard) @ 6477', 6483', 6486', 6498', 6500',
 W/1 SPF
 Ac. 250 gals.
 Frac 10,000 gals oil + 10,000# sd.
 Re-Ac. 3000 gals.
 Set Pkr @ 6200',
 Perf (Blinebry)@ 5710', 5712', 5733', 5736',
 5781', 5783' & 5800' W/1 SPF
 Ac. 500 gals,
 Frac 10,000 gals oil + 10,000# sd.
 Pulled Pkr.