

OF CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-7

OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
B-935

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

21c. ☒ WELL ☐ GAS WELL ☐ OTHER-

Name of Operator

EXXON CORPORATION

Address of Operator

Box 1600, MIDLAND, TEXAS 79702

Location of Well

UNIT LETTER J 1980 FEET FROM THE SOUTH LINE AND 1980 FEET FROM THE EAST LINE, SECTION 10 TOWNSHIP 21 S RANGE 37 E N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name

NEW MEXICO STATE

9. Well No.

6

10. Field and Pool, or Whdeat

BLINEBRY
DRINKARD

15. Elevation (Show whether DF, RT, GR, etc.)

RDB 3467

12. County

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☒
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPER. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

1. LOAD AND KILL DRINKARD. OPEN TBG/CSG ANNUALLY. CIRE WELL.
2. PULL LONG & SHORT STRING. MILL OUT PERMANENT PKR OR PUSH TO 6770' OR LOWER.
3. PERF BLINEBRY-5874-5955, 6055-6115' TOTAL OF 715 SHOTS.
DRINKARD-6490-6550, 6610-6624, 6630-6640, 6647-6695, 6710, 6720'- TOTAL OF 70 SHOTS.
4. TEST TBG TO 5000'. SET RBP @ 6740'- SPOT 200 GAL 20% NEHCL. ACIDIZE W/3400 GAL INHIBITED 20% NEHCL. PULL W/PAND SET RBP @ 6575'. SPOT 200 GAL INHIBITED 20% NEHCL. RAISE AND SET PKR AT 6350'. ACIDIZE W/3400 GAL INHIBITED 20% NEHCL.
5. RAISE AND SET RBP @ 6150'. SPOT 200 GAL INHIBITED 20% NEHCL. ACIDIZE W/3400 GAL INHIBITED 20% NEHCL. RAISE AND SET BP @ 6000'- SPOT 200 GAL INHIBITED 20% NEHCL. RAISE AND SET PKR AT 5865'- ACIDIZE W/4600 GAL INHIBITED 20% NEHCL. SET RBP @ 5860'- SPOT 200 GAL INHIBITED 20% NEHCL. RAISE AND SET PKR AT 5600'- ACIDIZE W/4000 GAL INHIBITED 20% NEHCL.
6. SET RBP AT 6200' W/PKR SET AT 5600'.
7. PLACE BLINEBRY ON PUMP.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. A. Lou TITLE SR. ADMIN DATE 6-10-85

JUN 14 1985

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT SUPERVISOR

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 13 1985

G.C.B.
HOBBS OFFICE