NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender-on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission

| | | Indicate Nature of Notice by | Checking B | lelow | |
|--|--|--|--|--|--|
| Notice of Intention to Change Plans | | Notice of Intention to Temporarily Abandon Well | | Notice of Intention to Drill Deeper | |
| NOTICE OF INTENTION O PLUG WELL | | Notice of Intention to Plug Back | * | Notice of Intention to Set Liner | |
| Notice of Intention o Squeeze | | Notice of Intention to Acidize | | Notice of Intention to Shoot (Nitro) | |
| OTICE OF INTENTION OF GUN PERFORATE | x | Notice of Intention (Other) | * | Notice of Intention (Other) | × |
| OIL CONSERVATIO ANTA FE, NEW ME | | Hobbs, New Hext.co | | April 3, 1956 | |
| entlemen: | | | | | |
| | tice of Intention to do | certain work as described below | | Well No | ······································ |
| Mar. Minds | (Company or Operator |) | | Well Noinin | (Unit) |
| 1/4(40-acre Subdivision | ¼ of Sec | , T, R, R | ,NMPM | , lbso | q |
| I.A. | Cou | | | | |
| 2. Perforate | FOLLOW and act deal at approximate Tabb sone from | L DETAILS OF PROPOSEI INSTRUCTIONS IN THE RU | LES AND Tool in | REGULATIONS) | , p ^a |
| 2. Perforate 3. mat. Tab. refined of 4. Ot inter 5. rerforate 6. ideal perfo gallone as 7. Hagh perfo | (FOLLOW sand and and and and approximations from packer at approximations from 10,000 packer at approximations from 10,000 posts | instructions in the Ruly 7475 and damp to the factor of th | y and it feet of and from in long to the second sec | regulations) The gas somest Commit on top. Acture with 10,000 galle | 10,000 |
| 2. Perforate 3. man Table refined of 4. Ot Unitor 5. Perforate 6. Hash perforations on 7. Hash perforations on L. Run in 3-4 | (FOLLOW sand and deal and approximate the perference of approximate the perference of approximate the perference of approximations from 10,000 pound at 10,000 | instructions in the Ruly 7475 and deep 10 a 6230 to 6330 with 1000 galions acid pounds same. Publicately 6000 and rule 500 to 5635 to 5695 at th 500 in. 1425 to 5695 at th 500 in. 1425 to 5695 at th 500 in. | y and it feet of and from in long sellons gallons | regulations) who gas someon compact on top. acture with 10,000 galls ser dual completion according to 50,00. a tid and fracture with | mbly, |
| 2. Perforate 3. mat. Tab. refined of 4. Ot inter 5. rerforate 6. ideal perfo gallone as 7. Hagh perfo | (FOLLOW sand and deal and approximate the perference of approximate the perference of approximate the perference of approximations from 10,000 pound at 10,000 | instructions in the Ruly 7475 and deep 10 a 6230 to 6330 with 1000 galions acid pounds same. Publicately 6000 and rule 500 to 5635 to 5695 at th 500 in. 1425 to 5695 at th 500 in. 1425 to 5695 at th 500 in. | y and it feet of and from in long sellons gallons | regulations) who gas somest compact on top. acture with 10,000 galls ser dual completion according to 50,00. a tid and fracture with add and fracture with | 10,000 |
| 2. Perforate 3. man Tab. refined of 4. Ot Inkor 5. Perforate 6. Hash perforate gallone an 7. Hash perforate gallone an 8. Pen in 3-4 | (FOLLOW some deal and approximate the some from perforations from stations from 10,000 pound to 10,000 pound to | instructions in the Ruly 7475 and deep 10 a 6230 to 6330 with 1000 galions acid pounds same. Publicately 6000 and rule 500 to 5635 to 5695 at th 500 in. 1425 to 5695 at th 500 in. 1425 to 5695 at th 500 in. | Tes and The feet of the in the test of the | regulations) who gas somes commit on top. acture with 10,000 galle rep dual completion according to 5030. a sid and fracture with bily and complete well. & Nofining Company | mbly, 10,000 |
| 2. Perforate 3. man Table refined of 4. Ot Inkor 5. Perforate 6. Man perforate gallone an 7. Man in 3-4 peroved | (FOLLOW some deal and approximate the some from perforations from stations from 10,000 pound to 10,000 pound to | instructions in the Ruly 7475 and damp 10 a 6270 to 6330. With 1000 galions acid pounds same. Parimetely 6000 and ruly from 5625 to 5675 and 5760 to 5830 with 500 in. Support dual exercises. | Test of feet of in in low in l | regulations) acture with 10,000 galls actu | 10,000 |