

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. BOX 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-06470

5. Indicate Type of Lease



STATE



FEE

6. State Oil & Gas Lease No.

22503

7. Lease Name or Unit Agreement Name

Northeast Drinkard Unit

8. Well No.

507

9. Pool name or Wildcat

Eunice N. Blinbry-Tubb-Drinkard

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:



OIL WELL



GAS WELL



OTHER

INJECTION

2. Name of Operator

Apache Corporation

3. Address of Operator

2000 Post Oak Blvd., Ste. 100, Houston, Texas 77056-4400

4. Well Location

Unit Letter

I

: 2100

Feet From The

South

Line and

760

Feet From The

East

Line

Section

10

Township

21S

Range

37E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3442' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:



Perform Remedial Work



Plug and Abandon



Temporarily Abandon



Change Plans



Pull or Alter Casing



Other

SUBSEQUENT REPORT OF:



Remedial Work



Altering Casing



Commence Drilling Operations



Plug and Abandonment



Casing Test and Cement Job



Other

Convert to Injection ✓

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work)
SEE RULE 1103.

10/6/98 MIRU. Pull and laydown rods

10/7/98 Finish POH w / rods & pump. Pump 60 BPW to kill well. ND WH, NU BOP.

10/8/98 RIH w / WS, bit & scraper, tag fill @ 6673'. Pumped 650 BPW & 1% KCL to reverse fill of plug. POH w / WS. RIH w / treating pkr to 5573' & set. Test backside to 500# - OK. POH w / WS & treating pkr. Prep to run injection string. SDFN

10/9/98 SITP - 140#. Bleed down & pump 50 bbls 1% KCL to kill. RIH w / tbg & pkr, set pkr @ 5580'. Pump 101 bbls pkr fluid. MIT test backside to 500# for 15 mins - MIT test good. SDFWE

10/12/98 Hook up surface injection lines. Put well on injection.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Debra J. Anderson

TITLE Engineering Technician

DATE 11/19/98

TYPE OR PRINT NAME

Debra J. Anderson

TELEPHONE NO. 713-296-6338

(This space for State Use)

ORIGINAL SIGNED BY

GARY WINK

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY

DEC 04 1998

JCS

[Handwritten initials]