



Land Office Las Cruces
Lease No. 031741 (b)
Unit H

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT.....	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY.....	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL.....	<input type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 5, 1953

Well No. 1 is located 1715 ft. from N line and 409 ft. from E line of sec. 10
10 - 10 Sec. 10 (1/4 Sec. and Sec. No.)
21-8 (Twp.) 37-1 (Range) 10-1 (Meridian)
Brinkard (Field) Lea (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 3424 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with rotary tools at the above location to a depth of approximately 6050', or to a depth sufficient to complete in the Brinkard horizon. All casing points will be completed in accordance with approved methods of the U. S. Geological Survey and any other special requirements will be complied with.

It is planned to use the following casing pattern: 10 5/4" casing to be set at approximately 200' and cemented with 200 sacks, cement to be circulated to the surface, 7 5/8" casing to be set at approximately 3100' and cemented with 1000 sacks or sufficient cement to protect the salt section, and 5 1/2" casing to be set at approximately 5500' and cemented with 400 sacks.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Loss years agent for J. J. Rodgers

Address Box 1713
Mobbs, New Mexico

By J. J. Rodgers

Title J. J. Rodgers - Operator

ELF
12/11/69
ABOVE DATE DOES NOT
INDICATE WHEN
CONFIDENTIAL LOSS
WILL BE RELEASED