

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL GAS
PRODUCTION OFFICE	
OPERATOR	

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE O. C. C.

## MISCELLANEOUS NOTICES Dec 9 9 23 AM '63

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the school on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICORoswell, New Mexico  
(Place)December 6, 1963  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company

State (Sec. 2)

Well No. 16

in K

(Company or Operator)

Lease

(Unit)

NE 1/4 SW 1/4 of Sec. 2, T. 21 S, R. 37 E, NMPM., Hare Pool  
(40-acre Subdivision)

Lea

County.

**RECOMPLETE FROM HARE TO DRINKARD:**FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Pull tubing.
2. Run GR/N/CCL Survey from 7985' (PBSD) to intermediate casing (3150'±).
3. Set CIBP at 7500' on wireline and cap with one sack cement.
4. Perforate selected intervals from approximately 6650' to 6760'.
5. Run 3" XL tubing with full-bore retrievable cementer and set packer at approximately 6600'.
6. Spot 250 gallons 15% BDA with Fe additive and load tubing with lease crude containing 1/20#/gallon Mark II Adomite, let acid soak overnight and displace acid to formation.
7. Fracture treat down 3" tubing with 20,000 gallons lease crude containing 1# 20-40 mesh sand and 1/20# Mark II Adomite per gallon.
8. Pull tubing and full-bore retrievable cementer.
9. Run production equipment. Swab test for sand flowback and place well on production.

Approved....., 19.....  
Except as follows:Approved  
OIL CONSERVATION COMMISSIONBy: Leslie A. Clements

Title.....

Shell Oil Company

Company or Operator

By: R. A. Lowery Original Signed By

R. A. Lowery

Position: District Exploitation Engineer

Send Communications regarding well to:

Name: Shell Oil CompanyAddress: Box 1858 Roswell, New Mexico