

...Depth Cleaned Out.....5904

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 5925 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing August 25, 1956

OIL WELL: The production during the first 24 hours was 276 barrels of liquid of which 95 % was
was oil; % was emulsion; 5 % water; and % was sediment. A.P.I.
Gravity 37.2° API

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid-Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefec
T. Queen Dolomite 3427 (+69)	T. Ellenburger	T. Point Lookout
T. Grayburg Dolomite 3786 (-290)	T. Gr. Wash	T. Mancos
T. San Andres Dolomite 4004 (-798)	T. Granite	T. Dakota
T. Glorieta Dolomite 5260 (-1764)	T. Penrose Sand 3625 (-129)	T. Morrison
T. Drinkard	T. Paddock Dolo. 5320 (-1824)	T. Penn
T. Tubbs	T. Blinberry Dolo. 5710 (-2214)	
T. Abo		
T. Penn		
T. Miss		

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	150	150	Surface sands, caliche				
150	1140	990	Red Beds				
1140	3118	1978	Anhydrite				
3118	5924	2806	Dolomite				
		5924					

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

September 5, 1956 (Date)
Company or Operator Shell Oil Company Address Box 1957, Hobbs, New Mexico
Name B. Nevill Position or Title Division Exploitation Engineer