	· · · · · ·	Approval expires 12-31-60.
rm 9-331 a Feb. 1951)	N TRIPLICATE)	Land Office
	D STATES	Lease No. LC 031741 0
	· · · · · · · · · · · · · · · · · · ·	Unit
	OF THE INTERIOR	
GEOLOG	ICAL SURVEY	
	1 mil 2 17	
SUNDRY NOTICES AN		
NOTICE OF INTENTION TO DRILL		ER SHUT-OFF DTING OR ACIDIZING
NOTICE OF INTENTION TO CHANGE PLANS	11	ERING CASING
NOTICE OF INTENTION TO TEST WATER SHOT-OFF	SUBSEQUENT REPORT OF RE-L	RILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		NDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING		RY
NOTICE OF INTENTION TO MERINAR MORP Ingback	K	
(INDICATE ABOVE BY CHECK MARK N	ATURE OF REPORT, NOTICE, OR OT	HER DATA)
(INDICATE ABOVE BY CHILOR MANTA		Karch 22, 19 57
Vell No		from $\begin{bmatrix} E \\ I \end{bmatrix}$ line of sec
13/4 See 3 21 3 37 5		
(14 Sec. and Sec. No.)	Range) (Meridian)	New Nexico
15		波·微波 小麦香辛 合义
The elevation of the derrick floor above sea leve		(State or Territory)
(County or (Field) (County or The elevation of the derrick floor above sea leve DETAIL State names of and expected depths to objective sands; show sizes ing points, and all other The present production of the ping. It is proposed to plugbe	el is ft. S OF WORK weights, and lengths of propose her important proposed work) SOVE WELL IN CK CO CHE BLINE	(State or Territory) d casings; indicate mudding jobs, cement- 5.6 30 10 and 30 BWFD bry formation and fo-
(County or (Field) (County or The elevation of the derrick floor above sea leve DETAIL State names of and expected depths to objective sands; show sizes ing points, and all ot	el isft. S OF WORK weights, and lengths of proposed her important proposed work) boxs well is inchry Pool in with commt re ith 150 sacks c water with oil bridge plugs.	(State or Territory) d casings; indicate mudding jobs, cement- 5.6 BOFD and 30 BWFD bry formation and re- the following manner: tainer. Set retainer mont, leaving 5' con Intervals performe erforate 5753-5604',
(Field) (County or (County or (County or (County or (County or DETAIL State names of and expected depths to objective sands; show sizes ing points; and all of The present production of the ping. It is proposed to pingbe plete this well in the Terry 31 1 rode and tubing, rerun tubing 0580', equeoze below retainer is on top of retainer. Displaced treated will be separated by 1 dise with 1000 gallons 15% LST atment. Perforate 5640-5974', 5980', treat as above. Drill it. A subsequent report will be a lunderstand that this plan of work must receive approval in	el isft. S OF WORK weights, and lengths of proposed her important proposed work) above well is in the weight is with compating with compating with compating of the sile bridge plugs. F a scid and sand treat as above. bridge plugs.	(State or Territory) d casings; indicate mudding jobs, cement- 5.6 BOFD and 30 BoFD bry formation and re- the following manner: tainer. Set retainer ement, leaving 5' con . Intervals perforet erforate 5753-5604', frac with 6000 gallon Perforate 5904-5945 recover oil load, and completion of work. before operations may be commenced.
(Field) (County or The elevation of the derrick floor above sea leve DETAIL State names of and expected depths to objective sands: show size ing points, and all other The present production of the ping. It is proposed to plughe plete this well in the Terry H I rode and tubing, rerun tubing 6580', equence below retainer is on top of retainer. Displaced treated will be separated by H dise with 1000 gallons 155 Liff atment. Perforate 5840-5974', 5980', treat as above. Drill atment. Perforate S840-5974', Life A subsequent report will be a I understand that this plan of work must receive approval in Company Centinental Gil Company	el isft. S OF WORK weights, and lengths of proposed her important proposed work) above well is in the weight is with compating with compating with compating of the sile bridge plugs. F a scid and sand treat as above. bridge plugs.	(State or Territory) d casings; indicate mudding jobs, cement- 5.6 BOFD and 30 BoFD bry formation and re- the following manner: tainer. Set retainer ement, leaving 5' con . Intervals perforet erforate 5753-5604', frac with 6000 gallon Perforate 5904-5945 recover oil load, and completion of work. before operations may be commenced.
(Field) (County or The elevation of the derrick floor above sea leve DETAIL State names of and expected depths to objective sands: show size ing points, and all other The present production of the ping. It is proposed to plughe plete this well in the Terry H I rode and tubing, rerun tubing 6580', equence below retainer is on top of retainer. Displaced treated will be separated by H dise with 1000 gallons 155 Liff atment. Perforate 5840-5974', 5980', treat as above. Drill atment. Perforate S840-5974', Life A subsequent report will be a I understand that this plan of work must receive approval in Company Centinental Gil Company	el isft. S OF WORK weights, and lengths of proposed her important proposed work) above well is in the weight is with compating with compating with compating of the sile bridge plugs. F a scid and sand treat as above. bridge plugs.	(State or Territory) d casings; indicate mudding jobs, cement- 5.6 BOFD and 30 BoFD bry formation and re- the following manner: tainer. Set retainer ement, leaving 5' con . Intervals perforet erforate 5753-5604', frac with 6000 gallon Perforate 5904-5945 recover oil load, and completion of work. before operations may be commenced.
(Field) (County or (County or (County or (County or (County or DETAIL State names of and expected depths to objective sands; show sizes ing points; and all of The present production of the ping. It is proposed to pingbe plete this well in the Terry 31 1 rode and tubing, rerun tubing 0580', equeoze below retainer is on top of retainer. Displaced treated will be separated by 1 dise with 1000 gallons 15% LST atment. Perforate 5640-5974', 5980', treat as above. Drill it. A subsequent report will be a lunderstand that this plan of work must receive approval in	el isft. S OF WORK weights, and lengths of proposed her important proposed work) a bown well is in the second residence of the Sline in the second residence of the second residence of the second in the second residence of t	(State or Territory) d casings; indicate mudding jobs, cement- 5.6 BOFD and 30 BoFD bry formation and re- the following manner: tainer. Set retainer ement, leaving 5' con . Intervals perforet erforate 5753-5604', frac with 6000 gallon Perforate 5904-5945 recover oil load, and completion of work. before operations may be commenced.
(Field) (County or The elevation of the derrick floor above sea leve DETAIL State names of and expected depths to objective sands; show sizes ing points; and all of The present production of the ping. It is proposed to pinghs plete this well in the Terry 31 1 rode and tubing, rerun tubing 0580', equeoze below retainer is on top of retainer. Displaced treated will be separated by 1 dise with 1000 gallons 15% 1577 atment. Perforate 5860-5874', 5-5980', treat as above. Drill it. A subsequent report will be a I understand that this plan of work must receive approval in Company Centinent al Cill Company Address Box 68	el isft. S OF WORK weights, and lengths of proposed her important proposed work) Bove well is to the Sline linebry Pool in with count re- with count re- with 150 sacks c water with oil bridge plugs. F a scid and sand treat as above. bridge plugs, bridge plugs, which is cological Survey By	(State or Territory) d casings; indicate mudding jobs, cement- 5.6 BOFD and 30 BoFD bry formation and re- the fellowing manner: tainer. Set retainer ement, leaving 5' cem . Intervals perforet erforate 5753-5604', frac with 6000 gallon Perforate 5904-5945 recover oil lead, and completion of work. before operations may be commenced.
(Field) (County or (Field) (County or The elevation of the derrick floor above sea leve DETAIL State names of and expected depths to objective sander; show sizes ing points, and all of The present production of the ping. It is proposed to plughe plate this well in the Perry 31 1 rode and tubing, rerun tubing 6580', equeeze below retainer is on top of retainer. Displaced treated will be separated by dise with 1000 gallons 155 LUTE atment. Perforate 5840-5674', 5-3980', treat as above. Drill at. A subsequent report will be I understand that this plan of work must receive approval in Company Centinental Cill Company Address Sex 68	el isft. S OF WORK weights, and lengths of proposed her important proposed work) Bove well is to the Sline linebry Pool in with count re- with count re- with 150 sacks c water with oil bridge plugs. F a scid and sand treat as above. bridge plugs, bridge plugs, which is cological Survey By	(State or Territory) d casings; indicate mudding jobs, cement- 5.6 BOFD and 30 BNFD bry formation and re- the fellowing manner: tainer. Set retainer ement, leaving 5' con Intervals perforet erforate 5753-5604', frac with 6000 gallon Perforate 5904-5945 recover oil lead, and completion of work. before operations may be commenced.