

**(SUBMIT IN TRIPLICATE)**

Land Office Las Cruces

Lease No. 031741 (b)

Unit 2

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Subsequent Report of Dual Completion

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 11 1962

Well No. 13 is located 660 ft. from N line and 660 ft. from E line of sec. 3

SE/4 Sec. 3                      21-S                      37-E                      14PM  
(¼ Sec. and Sec. No.)                      (Twp.)                      (Range)                      (Meridian)

Drinkard                      Lea                      New Mexico  
(Field)                      (County or Subdivision)                      (State or Territory)

The elevation of the derrick floor above sea level is 3466 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

BEFORE WORKOVER: TD 6760', FB 6749', DP 10', ELEV 3456' GL, CSG PT. 7" AT 6759',  
PAY DRINKARD 6645-6705', PERFS: 6645-60', 6664-79', 6683-94', 6698-6705'. PMP  
7 BO, 4 B; W/45.6 MCFG IN 24 HRS. GOR 6514', DOR 7 BO, DAILY ALLOW 7 BO.

WORK DONE: SET BP AT 6635', PERF DRINKARD 6512-20', 6525-28', 6532-38', 6546-50', 6553-55', 6556-58', 6563-65', 6568-75', 6583-85', 6589-93', 6598-6602', 6605-09', 6616-28', W/2 JSPP. SPOT 200 GAL ACID ACROSS PERFS & LEFT OVERNIGHT. THRD DRK 6512-6628', W/1000 GAL 15% REG ACID FOL BY 20,000 GAL SOL-U-FRAC USING 15,000 LBS SD & 80 BALL SEALERS IN 4 STAGES. PULLED NET BP.

AFTER WORKOVER: TD, PB, DF, BLEV & CHSING PT - SAME. TAY DRINKARD 6512-6705'.  
PERFS: SAME AS ABOVE (6512-6705'). ON POT PL 73 BO, 5 BAW IN 15.5 HRS, W/GAS  
AT RATE OF 44.3 MCF/D ON 25/64" CHL. GOR 392, MOR 113. EST (see reverse side)

**I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.**

Company Continental Oil Company

Address Box 68

Dunice, New Mexico

By H. K. Tucker

Title **District Superintendent**

0/3 USGS; NADOC-2; WMA; FIFE; PAN AG-  
HUBS-3; ATL-RES-2; CHIEF. OIL CO-HOUST,  
AID-1 en.