

Form 9-381a
(March 1942)

(SUBMIT IN TRIPLICATE)

Land Office Las Cruces

Lease No. 091741 (b)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED

DEC 14 1950

SUNDRY NOTICES AND REPORTS ON WELLS

NEW MEXICO COMMISSION
HOBBS OFFICE

NOTICE OF INTENTION TO DRILL.....	☒	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

U. C. Hawk 8-3 No. 1-E Hobbs, New Mexico December, 19 50

Well No. 1-E is located 910 ft. from SW line and 660 ft. from E line of sec. 3

SE 1/4 Sec. 3 21 3 17R R4N
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Duncan Lee New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with rotary tools at the above location to a total depth of approximately 7890'. All casing points will be cemented in accordance with approved methods of the U.S. Geological Survey and any other special requirements will be complied with.

It is planned to use the following casing pattern: 10 3/4" casing to be set at approximately 250' and cemented with 250 sacks. Cement to be circulated to surface. 7 5/8" casing to be set at approximately 3100' and cemented with approximately 990 sacks or sufficient cement to protect the salt section as determined by caliper survey. 5 1/2" casing to be set at approximately 7890' and cemented with approximately 550 sacks as determined by caliper survey. 5 1/2" casing to be perforated opposite pay section.

I understand that the plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box CC

Hobbs, New Mexico

By E. L. Shaper

Title District Superintendent

