

(SUBMIT IN TRIPLICATE)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 031741 (b)
Unit N.M.F.U.

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	X
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

W. C. Hawk B-3 No. 3-E Hobbs, New Mexico May 16, 19 51

Well No. 3-E is located 2970 ft. from N line and 660 ft. from E line of sec. 3

SE/4 Sec. 3
(1/4 Sec. and Sec. No.)

21S
(Twp.)

37E
(Range)

N.M.P.M.
(Meridian)

North Brunson
(Field)

Lea

(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 3480 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set 7 5/8" casing at 3149', using 6 centralizers and 57 scratchers, and cemented with 1110 sax 4% Gel, 100 sax neat, and 25 sax Mobilite. Plug down 8:00 A.M. 5-11-51. Top of cement by temperature survey 975'.

On 5-13-51, after 48 hrs. WOC, tested casing with 1200# for 30 mins. before drilling plug, final pressure 1190#. Found top of cement inside pipe at 3117'. Drilled out plug and tested casing with 1200# for 30 mins., final pressure 1180#.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box CC

Hobbs, New Mexico

By [Signature]

Title Asst. District Superintendent

DUPLICATE

Budget Bureau 42-R388.2
Approval expires 12-31-52

Form 9-351a
(Feb. 1951)

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Lee, New Mexico

Lease No. 0312

Unit _____

RECEIVED
MAY - 4 1951
OIL CONSERVATION COMMISSION
HOBBS OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

W. C. Hawk B-3 No. 3-E

Hobbs, New Mexico April 30, 19 51

Well No. 3-E is located 2970 ft. from N line and 460 ft. from E line of sec. 3

35/4 Sec. 3
(1/4 Sec. and Sec. No.)

21S
(Twp.)

37E
(Range)

N.M.P.M.
(Meridian)

North Brunson
(Field)

Lee
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with rotary tools at the above location to a total depth of approximately 8300'. All casing points will be cemented in accordance with approved methods of the U.S. Geological Survey and any other requirements will be complied with.

It is planned to use the following casing pattern: 10 3/4" casing to be set at approximately 250' and cemented with 250 sacks; cement to be circulated to surface. 7 5/8" casing to be set at approximately 3100' and cemented with approximately 300 sacks or sufficient cement to protect the salt section. 5 1/2" casing to be set at total depth and cemented with approximately 720 sacks as determined by survey. 5 1/2" casing to be perforated opposite pay section.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Buz. CG

Hobbs, New Mexico

By D. T. Jacobs

Title Act. District Superintendent