

UNITED STATES
DEPARTMENT OF THE INTERIOR RECEIVED
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

CONOCO INC.

3. ADDRESS OF OPERATOR

P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2970' FSL + 510' FEL

AT TOP PROD. INTERVAL: -

AT TOTAL DEPTH: -

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) PERF ADDITIONAL PAY + STIMULATE. ☒

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU. INSTALL BOP. CLEAN OUT TO 8005'. PERFORATE CONNELL FROM 7960' TO 7967'. SET PACKER @ 7900'. ACIDIZE 7960'-7967' w/16 BBLs. 15% HCL-NE-FE. FLUSH w/35 BBLs. 2% KCL TFW. SWAB. SET RBP @ 7660'. SPOT 4 BBLs. 15% HCL-NE-FE FROM 7473' to 7641'. PERFORATE UPPER MCKEE FROM 7499' TO 7641'. SET PACKER @ 7350'. ACIDIZE 7499'-7641' w/28 BBLs. 15% HCL-NE-FE. FLUSH w/35 BBLs. 2% KCL TFW. SWAB. RELEASE PACKER AND BRIDGE PLUG. RUN PRODUCTION EQUIP.

TEST.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Administrative Supervisor DATE 6/10/83

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

[Signature]

AUG 24 1983

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO