

NO. OF COPIES RECEIVED	
DISTRIBUTION	
DATE	
FILE	
S.G.S.	
AND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Supersedes Old
C-102 and C-103
Effective 1-1-85

SUNDRY NOTICES AND REPORTS ON WELLS DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.		5a. Indicate Type of Lease State ☐ Fee ☒ 5. State Oil & Gas Lease No.
OIL WELL ☒ GAS WELL ☐ OTHER ☐ Name of Operator SHELL OIL COMPANY Address of Operator P. O. BOX 991, HOUSTON, TX 77001 Location of Well UNIT LETTER S 1980 FEET FROM THE SOUTH LINE AND 1980 FEET FROM THE WEST LINE, SECTION 3 TOWNSHIP 21 S RANGE 37 E NMPM.		7. Unit Agreement Name 8. Farm or Lease Name LIVINGSTON 9. Well No. 1 10. Field and Pool, or Wildcat Drinkard
15. Elevation (Show whether DF, RT, GR, etc.) 3435' DF		12. County LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐		SUBSEQUENT REPORT OF: PLUG AND ABANDON ☐ CHANGE PLANS ☐ OTHER ☐ REMEDIAL WORK ☒ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOBS ☐ OTHER ☐ ALTERING CASING ☐ PLUG AND ABANDONMENT ☒
---	--	---

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

ACIDIZE DRINKARD ZONE

- 5-2-80: RUPU (DA&S). Pld rods & tbg.
- 5-3-80: Ran (Baker) FB retrievable cementer on 2" tbg & set @6655'. RU (Western CO) acid truck. Acid treated openhole 6674-6700' w/1000 gals 15% NE acid @Max/Min press 3600/1500 psi. AIR 3 BPM. ISIP 200 psi. Pld tbg & pkr. Ran (Baker) RBP & pkr on 2" tbg. Set RBP @6650' & pkr @6475'. Acid treated perfs 6628-6640' w/2000 gals 15% NE acid in 2 - 1000 gal stages, mixing & ppg 150# benzoic acid & 300# rock salt between stages @Max/Min press 900/0. AIR 3.8 BPM. ISIP 100 psi. Pld tbg, pkr & RBP. SDON.
- 5-4-80: SD. Cost: \$6350.
- 5-5-80: Ran 1 jt 2 1/2" OPMA w/top 3' perforated, 2" SN + 208 jts 2" EUE 8rd thread tbg 6512' & hung @6522', OPMA @6492'-6522', SN @6491', 3 - 2" x 6' subs on top of string. Ran 2" x 1 1/2" x 16' Continental-Emsco pump w/1" x 10' dip tube on 210 - 3/4", 45 - 7/8" rods. 1 - 7/8" x 4' & 1 - 7/8" x 6' subs on top of string. RDP. Started well to ppg.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed A. J. Fore TITLE SR. ENGR. TECH. DATE 6/27/80

APPROVED BY Jerry Sexton TITLE Dist. L. Supv. DATE 7 1980

CONDITIONS OF APPROVAL, IF ANY: