

NUMBER COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL GAS
PERFORATION OFFICE	
OPERATOR	

(Form C-102)
(Revised 7/1/52)

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the school on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	X	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nkro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER) TO FRAC	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

June 5, 1962
(Place)

Roswell, New Mexico
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company Livingston Well No. 2 in W
(Company or Operator) Lease (Unit)
SW 1/4 SE 1/4 of Sec. 3, T. 21S, R. 37E, NMPM., Drinkard Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

PROPOSED OPERATION

1. Drill out Model "D" packer.
2. Set Cast Iron Bridge Plug w/wire line at 6602'.
3. Perforate 6503' - 6508', 6522' - 6527', 6551' - 6560', 6565' - 6570' w/1 JSPP.
4. Run 3" XL tubing & full bore retrievable cementer, hydrotest tubing to 8000psi and set packer at 6450'.
5. Wash new perforations w/500 gallons BDA.
6. Treat new perforations w/20,000 gallons lease crude containing 1# sand & 1/20# Mark II per gallon.
7. Pull 3" tubing and full bore retrievable cementer.
8. Set Baker Model "D" packer w/side-door shocke & Baker seal assembly at 6400' w/wire line.
9. Run tubing and set in Model "D" packer.
10. Take packer leakage test.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Shell Oil Company
Company or Operator
By R. A. Lowery Original Signed By R. A. LOWERY
Position District Exploitation Engineer
Send Communications regarding well to:

Name Shell Oil Company
Address Box 1858, Roswell, New Mexico